

# Package ‘WindCurves’

January 20, 2025

**Type** Package

**Title** Tool to Fit Wind Turbine Power Curves

**Version** 0.2

**Date** 2022-04-30

**Author** Neeraj Bokde, Andres Feijoo

**Maintainer** Neeraj Bokde <neerajdhanraj@gmail.com>

**Description** Provides a tool to fit and compare the wind turbine power curves with successful curve fitting techniques. Facilitates to examine and compare the performance of a user-defined power curve fitting techniques. Also, provide features to generate power curve discrete points from a graphical power curves. Data on the power curves of the wind turbine from major manufacturers are provided.

**Imports** methods, readbitmap, grid

**License** GPL

**URL** <https://www.neerajbokde.in/vignette/2021-10-14-WindCurves/>

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.2

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-05-01 04:50:02 UTC

## Contents

fitcurve	2
img2points	2
pcurves	3
plot.fitcurve	4
validate.curve	4

**Index****6**


---

fitcurve	<i>A fitcurve function</i>
----------	----------------------------

---

**Description**

Fits the power curve with Weibull CDF, Logistic and user defined techniques

**Usage**

```
fitcurve(data, MethodPath, MethodName)
```

**Arguments**

<code>data</code>	as input data.frame with two columns, i.e., wind speed and wind power
<code>MethodPath</code>	as path of a code for user defined curve fitting technique
<code>MethodName</code>	as name of the user defined curve fitting technique

**Value**

fitted curves and corresponding discrete fitted values

**Examples**

```
data(pcurves)
s <- pcurves$Speed
p <- pcurves`Nordex N90`
da <- data.frame(s,p)
fitcurve(da)
```

---

img2points	<i>A function to capture Speed Vs Power discrete points from power curve image</i>
------------	--

---

**Description**

A function to capture Speed Vs Power discrete points from power curve image

**Usage**

```
img2points(imagePath, n)
```

**Arguments**

<code>imagePath</code>	as Path of a power curve image
<code>n</code>	as number of points to be captured from the curve image (default value is 15)

**Value**

data.frame with two columns, i.e., wind speed and wind power

**Examples**

```
## Not run:  
# to import image from system 'extdata' folder.  
# user can directly specify the path of the image in 'img2points()' .  
imagePath <- system.file("extdata","powcurve.jpeg", package="WindCurves")  
img2points(imagePath)  
## End(Not run)
```

---

pcurves

*Wind Turbine Power Curves*

---

**Description**

Data on the power curves of wind turbine from four major manufacturers: Siemens, Vestas, RE-power and Nordex. Represents wind turbine power output in 'kW' against wind speed in 'metres per second'.

**Usage**

```
data(pcurves)
```

**Format**

An object of class `data.frame` with 25 rows and 7 columns.

**Source**

<https://goo.gl/tD2JW6>

**References**

Iain Staffell (2012) <https://goo.gl/tD2JW6>

**Examples**

```
data(pcurves)  
v <- pcurves$`Vestad V80`
```

---

<code>plot.fitcurve</code>	<i>A function to plot the curves fitted with fitcurve() function</i>
----------------------------	--

---

### Description

A function to plot the curves fitted with fitcurve() function

### Usage

```
## S3 method for class 'fitcurve'
plot(x, ...)
```

### Arguments

<code>x</code>	is object returned by fitcurve() function
<code>...</code>	Additional graphical parameters given to plot function.

### Value

Plot the curves fitted with fitcurve() function

### Examples

```
s <- pcurves$Speed
p <- pcurves$`Nordex N90`
da <- data.frame(s,p)
x <- fitcurve(da)
plot(x)
```

---

<code>validate.curve</code>	<i>A Validate.curve function</i>
-----------------------------	----------------------------------

---

### Description

Compares the performance of curve fitting techniques fitted in fitcurve() function

### Usage

```
validate.curve(x, MethodPath, MethodName)
```

### Arguments

<code>x</code>	is object returned by fitcurve() function
<code>MethodPath</code>	as path of a code for user defined error measure technique
<code>MethodName</code>	as name of the user defined error measure technique

**Value**

A comparison matrix in terms of various error measures.

**Examples**

```
s <- pcurves$Speed  
p <- pcurves$`Nordex N90`  
da <- data.frame(s,p)  
x <- fitcurve(da)  
validate.curve(x)
```

# Index

- \* **curves**
  - pcurves, [3](#)
- \* **power**
  - pcurves, [3](#)
- fitcurve, [2](#)
- img2points, [2](#)
- pcurves, [3](#)
- plot.fitcurve, [4](#)
- validate.curve, [4](#)