

Package ‘annotater’

July 14, 2025

Title Annotate Package Load Calls
Version 0.2.4
Description Provides non-invasive annotation of package load calls
such as `library()`, `p_load()`, and `require()` so that we can have an idea of what
the packages we are loading are meant for.
License MIT + file LICENSE
Encoding UTF-8
RoxygenNote 7.3.2
Imports dplyr, knitr, purrr, readr, rlang, rstudioapi, stringi,
stringr, tibble, tidyr
URL <https://github.com/luisDVA/annotater>, <https://annotater.liomys.mx>
BugReports <https://github.com/luisDVA/annotater/issues>
Suggests covr, rmarkdown, testthat
VignetteBuilder knitr
NeedsCompilation no
Author Luis D. Verde Arregoitia [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-9520-6543>>),
Juan Cruz Rodriguez [ctb],
Hadley Wickham [ctb]
Maintainer Luis D. Verde Arregoitia <luis@liomys.mx>
Repository CRAN
Date/Publication 2025-07-14 19:10:13 UTC

Contents

align_annotations	2
annotate_active_file	3
annotate_data_active_file	3
annotate_fun_calls	3
annotate_fun_calls_active_file	4

annotate_pkg_calls	4
annotate_pkg_datasets	5
annotate_repostitle	6
annotate_repostitle_active	6
annotate_repos_active_file	7
annotate_repo_source	7
annotate_r_version	8
annotate_script	8
check_pkgs	8
expand_metapackages	9
expand_metapackages_active_file	9
get_pkg_datasets	10
match_pkg_names	10
pkg_version	11
repo_details	11
Index	12

align_annotations	<i>Vertical alignment of package annotations</i>
-------------------	--

Description

Internal helper function, based on ‘unheadr::regex_valign‘

Usage

```
align_annotations(  
  annot_string,  
  regex_ai = paste0("(?!\\s))(?!\\s)(?=\\sCRAN\\s|",  
    "\\sBiocon|\\snot\\sinstall|", "\\s\\s\\s\\s[|\\sPosit R)"),  
  sep_str = ""  
)
```

Arguments

- annot_string Character vector with annotated package calls.
- regex_ai Custom regular expression to match lines with package annotations.
- sep_str Whitespace separator.

Value

A character vector with vertically aligned package calls.

annotate_active_file *Annotate active file*

Description

Annotates package load calls in the active .R file

Usage

annotate_active_file()

Value

No return value, wraps [annotate_pkg_calls()] for access via Addin

annotate_data_active_file
 Annotate loaded data in active file

Description

Annotates package load calls with loaded datasets in the active .R file

Usage

annotate_data_active_file()

Value

No return value, wraps [annotate_pkg_datasets()] for access via Addin

annotate_fun_calls *Annotate function calls*

Description

Annotate function calls

Usage

annotate_fun_calls(string Og)

Arguments

string Og text string (script) with package load calls

Value

text string with function call annotations. Will make note of packages not currently installed. Lines with existing comments or annotations are ignored by the regular expression that matches package names. Be aware that package-specific methods (e.g., print or summary methods) will be annotated too.

Examples

```
test_string <- c("library(boot)\nrequire(lattice)\ncanonical.theme()")
cat(annotate_fun_calls(test_string))
```

```
annotate_fun_calls_active_file
```

Annotate function calls in active file

Description

Annotates package load calls with the used functions of each package in the active .R file

Usage

```
annotate_fun_calls_active_file()
```

Value

No return value, wraps [annotate_fun_calls()] for access via Addin

```
annotate_pkg_calls
```

Annotate package calls

Description

Annotate package calls

Usage

```
annotate_pkg_calls(string Og, pkg_field = "Title")
```

Arguments

string Og	Text string (script) with package load calls.
pkg_field	Field from package description to retrieve, defaults to "Title"

Value

Text string with package Title annotations. Will make note of packages not currently installed.

Examples

```
test_string <- c("library(boot)\nrequire(tools)")
annotate_pkg_calls(test_string)
```

annotate_pkg_datasets *Annotate package datasets*

Description

Annotate package datasets

Usage

```
annotate_pkg_datasets(string Og)
```

Arguments

string Og text string (script) with package load calls

Details

No support for **pacman** package loading at this time.

Value

text string with annotations for datasets loaded from packages explicitly, lazily, or through name-spacing. Will make note of packages not currently installed. Lines with existing comments or annotations are ignored.

Examples

```
test_string <- c("library(tidyr)\nlibrary(purrr)\ndata(construction)\nsummary(fish_encounters)")
annotate_pkg_datasets(test_string)
```

annotate_repostitle *Annotate package titles and repository sources*

Description

Annotate package titles and repository sources

Usage

```
annotate_repostitle(string Og)
```

Arguments

string Og Text string (script) with package load calls.

Details

Some annotations may be long, check for possible line breaks introduced into your script.

Value

Text string with package titles and package repository source annotations. Will make note of packages not currently installed. Lines with existing comments or annotations are ignored by the regular expression that matches package names. Also ignores base packages.

Examples

```
test_string <- c("library(knitr)\nrequire(datasets)")
annotate_repostitle(test_string)
```

annotate_repostitle_active
 Annotate titles and repositories in active file

Description

Annotates package load calls with package titles and repository details in the active .R file

Usage

```
annotate_repostitle_active()
```

Value

No return value, wraps [annotate_repostitle()] for access via Addin

annotate_repos_active_file

Annotate repositories in active file

Description

Annotates package load calls with repository details in the active .R file

Usage

```
annotate_repos_active_file()
```

Value

No return value, wraps [annotate_repo_source()] for access via Addin

annotate_repo_source *Annotate repository sources*

Description

Annotate repository sources

Usage

```
annotate_repo_source(string Og)
```

Arguments

string Og text string (script) with package load calls

Value

text string with package repository source annotations. Will make note of packages not currently installed. Lines with existing comments or annotations are ignored by the regular expression that matches package names. Also ignores base packages. Local installs now annotated as such.

Examples

```
test_string <- c("library(knitr)\nrequire(datasets)")
annotate_repo_source(test_string)
```

annotate_r_version	<i>Annotate R Version</i>
--------------------	---------------------------

Description

Annotate R Version

Usage

```
annotate_r_version()
```

annotate_script	<i>Annotate script</i>
-----------------	------------------------

Description

Annotate script

Usage

```
annotate_script(script_file, pkg_field = "Title")
```

Arguments

script_file	Path to an R script.
pkg_field	Field from package description to retrieve, defaults to "Title".

Value

Prints the annotated script to the console.

check_pkgs	<i>Check if packages are installed</i>
------------	--

Description

Check if packages are installed

Usage

```
check_pkgs(pkgvec)
```

Arguments

pkgvec	Vector of package names
--------	-------------------------

Value

A data frame with installation status for packages in the input text.

expand_metapackages	<i>Expand metapackages</i>
---------------------	----------------------------

Description

Expand metapackages

Usage

```
expand_metapackages(string Og)
```

Arguments

string Og text string (script) with package load calls

Value

Text string with metapackage load calls replaced by multiple separate calls to the core packages that make up the metapackage. Core packages will be fenced in four commenting symbols and the order follows the attachment order from each metapackage. Will make note of metapackages not currently installed.

Examples

```
test_string <- c("library(tidyverse)")
expand_metapackages(test_string)
```

expand_metapackages_active_file	<i>Expand metapackages in active file</i>
---------------------------------	---

Description

Replaces metapackage load calls in the active .R file with multiple separate calls to its core packages.

Usage

```
expand_metapackages_active_file()
```

Value

No return value, wraps [expand_metapackages()] for access via Addin

get_pkg_datasets	<i>Query data from packages</i>
------------------	---------------------------------

Description

Query data from packages

Usage

```
get_pkg_datasets(inst_pkgs)
```

Arguments

inst_pkgs Vector of package names

Value

A data frame with all the bundled data from the specified packages.

match_pkg_names	<i>Match package names</i>
-----------------	----------------------------

Description

Match package names

Usage

```
match_pkg_names(string Og)
```

Arguments

string Og Text string (script) with package load calls.

Value

A tibble with the package load calls and package names.

Examples

```
test_string <- c("library(boot)\nrequire(Matrix)")
match_pkg_names(test_string)
```

pkg_version	<i>Retrieve Package version</i>
-------------	---------------------------------

Description

Internal helper function.

Usage

```
pkg_version(pkgs_col)
```

Arguments

pkgs_col Package name.

Value

A character vector with the package version.

repo_details	<i>Retrieve repo details</i>
--------------	------------------------------

Description

Internal helper function.

Usage

```
repo_details(pkgs_col)
```

Arguments

pkgs_col Name of variable with the non-CRAN repos.

Value

A character vector of user names and repository names.

Index

`align_annotations`, [2](#)
`annotate_active_file`, [3](#)
`annotate_data_active_file`, [3](#)
`annotate_fun_calls`, [3](#)
`annotate_fun_calls_active_file`, [4](#)
`annotate_pkg_calls`, [4](#)
`annotate_pkg_datasets`, [5](#)
`annotate_r_version`, [8](#)
`annotate_repo_source`, [7](#)
`annotate_repos_active_file`, [7](#)
`annotate_repostitle`, [6](#)
`annotate_repostitle_active`, [6](#)
`annotate_script`, [8](#)

`check_pkgs`, [8](#)

`expand_metapackages`, [9](#)
`expand_metapackages_active_file`, [9](#)

`get_pkg_datasets`, [10](#)

`match_pkg_names`, [10](#)

`pkg_version`, [11](#)

`repo_details`, [11](#)