

Package ‘forestControl’

October 13, 2022

Type Package

Title Approximate False Positive Rate Control in Selection Frequency
for Random Forest

Version 0.2.2

Date 2022-02-09

Description Approximate false positive rate control in selection frequency for
random forest using the methods described by En-
der Konukoglu and Melanie Ganz (2014) <[arXiv:1410.2838](https://arxiv.org/abs/1410.2838)>.
Methods for calculating the selection frequency threshold at false positive rates
and selection frequency false positive rate feature selection.

Imports Rcpp, purrr, tibble, magrittr, dplyr

Suggests testthat, randomForest, ranger, parsnip, knitr, rmarkdown

License MIT + file LICENSE

Encoding UTF-8

URL <https://github.com/aberHRML/forestControl>

BugReports <https://github.com/aberHRML/forestControl/issues>

RoxygenNote 7.1.1

LinkingTo Rcpp

VignetteBuilder knitr

NeedsCompilation yes

Author Tom Wilson [aut, cre] (<<https://orcid.org/0000-0003-3112-4682>>),
Jasen Finch [aut]

Maintainer Tom Wilson <tpw2@aber.ac.uk>

Repository CRAN

Date/Publication 2022-02-09 10:50:02 UTC

R topics documented:

forestControl-package	2
extract_params	2
fpr_fs	3
selection_freqs	4
sft	4

Index

6

forestControl-package *False Positive Rate Control in Selection Frequency for Random Forest*

Description

This package is an implementation of the methods described by Ender Konukoglu and Melanie Ganz in *Konukoglu, E. and Ganz, M., 2014. Approximate false positive rate control in selection frequency for random forest. arXiv preprint arXiv:1410.2838* <https://arxiv.org/abs/1410.2838>.

extract_params *Extract forest parameters*

Description

For a `randomForest` or `ranger` classification object, extract the parameters needed to calculate an approximate selection frequency threshold

Usage

```
extract_params(x)
```

Arguments

x	a <code>randomForest</code> , <code>ranger</code> or <code>parsnip</code> object
---	--

Value

a list of four elements

- **F_n** The number of features considered at each internal node (`mtry`)
- **F_t** The total number of features in the data set
- **K** The average number of binary tests/internal nodes across the entire forest
- **T_r** The total number of trees in the forest

Author(s)

Tom Wilson <tpw2@aber.ac.uk>

Examples

```
library(randomForest)
data(iris)
iris.rf <- randomForest(iris[,-5], iris[,5], forest = TRUE)

iris.params <- extract_params(iris.rf)
print(iris.params)
```

fpr_fs

False Postivie Rate Feature Selection

Description

Calculate the False Positive Rate (FPR) for each feature using it's selection frequency

Usage

```
fpr_fs(x)
```

Arguments

x a randomForest or ranger object

Value

a tibble of selection frequencies and their false positive rate

Author(s)

Jasen Finch <jsf9@aber.ac.uk>

Examples

```
library(randomForest)
data(iris)
iris.rf <- randomForest(iris[,-5], iris[,5], forest = TRUE)

iris.features <- fpr_fs(iris.rf)
print(iris.features)
```

`selection_freqs` *Variable Selection Frequencies*

Description

Extract variable selection frequencies from `randomForest` and `ranger` model objects

Usage

```
selection_freqs(x)
```

Arguments

<code>x</code>	a <code>randomForest</code> or <code>ranger</code> object
----------------	---

Value

`tibble` of variable selection frequencies

Examples

```
library(randomForest)
data(iris)
iris.rf <- randomForest(iris[,-5], iris[,5], forest = TRUE)

iris.freqs <- selection_freqs(iris.rf)
print(iris.freqs)
```

`sft` *Selection Frequency Threshold*

Description

Determine the selecton frequency threshold of a model at a specified false positive rate

Usage

```
sft(x, alpha)
```

Arguments

<code>x</code>	a <code>randomForest</code> or <code>ranger</code> object
<code>alpha</code>	a false positive rate (ie, 0.01)

Value

a list of two elements

- **sft** The selection frequency threshold
- **probs_atsft** The estimated false positive rate

Author(s)

Tom Wilson <tpw2@aber.ac.uk>

Examples

```
library(randomForest)
data(iris)
iris.rf <- randomForest(iris[,-5], iris[,5], forest = TRUE)

# For a false positive rate of 1%
iris.sft <- sft(iris.rf, 0.01)
print(iris.sft)

# To iterate through a range of alpha values

alpha <- c(0.01,0.05, 0.1,0.15,0.2, 0.25)
threshold <- NULL
for(i in seq_along(alpha)){
  threshold[i] <- sft(iris.rf, alpha[i])$sft
}

plot(alpha, threshold, type = 'b')
```

Index

`extract_params`, [2](#)
`forestControl`-package, [2](#)
`fpr_fs`, [3](#)
`selection_freqs`, [4](#)
`sft`, [4](#)