

Package ‘nptest’

April 14, 2023

Type Package

Title Nonparametric Bootstrap and Permutation Tests

Version 1.1

Date 2023-04-14

Author Nathaniel E. Helwig <helwig@umn.edu>

Maintainer Nathaniel E. Helwig <helwig@umn.edu>

Description Robust nonparametric bootstrap and permutation tests for location, correlation, and regression problems, as described in Helwig (2019a) <[doi:10.1002/wics.1457](https://doi.org/10.1002/wics.1457)> and Helwig (2019b) <[doi:10.1016/j.neuroimage.2019.116030](https://doi.org/10.1016/j.neuroimage.2019.116030)>. Univariate and multivariate tests are supported. For each problem, exact tests and Monte Carlo approximations are available. Five different nonparametric bootstrap confidence intervals are implemented. Parallel computing is implemented via the ‘parallel’ package.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2023-04-14 19:50:02 UTC

R topics documented:

nptest-package	2
flipn	5
mcse	6
np.boot	8
np.cor.test	13
np.loc.test	16
np.reg.test	22
permn	27
plot	29
StartupMessage	31

Index

32

nptest-package	<i>Nonparametric Bootstrap and Permutation Tests</i>
-----------------------	--

Description

Robust nonparametric bootstrap and permutation tests for location, correlation, and regression problems, as described in Helwig (2019a) <doi:10.1002/wics.1457> and Helwig (2019b) <doi:10.1016/j.neuroimage.2019.116030>. Univariate and multivariate tests are supported. For each problem, exact tests and Monte Carlo approximations are available. Five different nonparametric bootstrap confidence intervals are implemented. Parallel computing is implemented via the 'parallel' package.

Details

The DESCRIPTION file:

```
Package:      nptest
Type:        Package
Title:       Nonparametric Bootstrap and Permutation Tests
Version:     1.1
Date:        2023-04-14
Author:      Nathaniel E. Helwig <helwig@umn.edu>
Maintainer:  Nathaniel E. Helwig <helwig@umn.edu>
Description: Robust nonparametric bootstrap and permutation tests for location, correlation, and regression problems, as described in Helwig (2019a) <doi:10.1002/wics.1457> and Helwig (2019b) <doi:10.1016/j.neuroimage.2019.116030>. Univariate and multivariate tests are supported. For each problem, exact tests and Monte Carlo approximations are available. Five different nonparametric bootstrap confidence intervals are implemented. Parallel computing is implemented via the 'parallel' package.
License:     GPL (>=2)
```

Index of help topics:

StartupMessage	Startup Message for nptest
flipn	Generate All Sign-Flips of n Elements
mcse	Monte Carlo Standard Errors for Tests
np.boot	Nonparametric Bootstrap Resampling
np.cor.test	Nonparametric Tests of Correlation Coefficients
np.loc.test	Nonparametric Tests of Location Parameters
np.reg.test	Nonparametric Tests of Regression Coefficients
nptest-package	Nonparametric Bootstrap and Permutation Tests
permn	Generate All Permutations of n Elements
plot	Plots Permutation Distribution for Nonparametric Tests

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

Maintainer: Nathaniel E. Helwig <helwig@umn.edu>

References

- Blair, R. C., Higgins, J. J., Karniski, W., & Kromrey, J. D. (1994). A study of multivariate permutation tests which may replace Hotelling's T₂ test in prescribed circumstances. *Multivariate Behavioral Research*, 29(2), 141-163. doi: 10.1207/s15327906mbr2902_2
- Carpenter, J., & Bithell, J. (2000). Bootstrap confidence intervals: when, which, what? A practical guide for medical statisticians. *Statistics in Medicine*, 19(9), 1141-1164. doi: 10.1002/(SICI)1097-0258(20000515)19:9%3C1141::AID-SIM479%3E3.0.CO;2-F
- Chung, E., & Romano, J. P. (2016). Asymptotically valid and exact permutation tests based on two-sample U-statistics. *Journal of Statistical Planning and Inference*, 168, 97-105. doi: 10.1016/j.jspi.2015.07.004
- Davison, A. C., & Hinkley, D. V. (1997). *Bootstrap Methods and Their Application*. Cambridge University Press. doi: 10.1017/CBO9780511802843
- DiCiccio, C. J., & Romano, J. P. (2017). Robust permutation tests for correlation and regression coefficients. *Journal of the American Statistical Association*, 112(519), 1211-1220. doi: 10.1080/01621459.2016.1202117
- Draper, N. R., & Stoneman, D. M. (1966). Testing for the inclusion of variables in linear regression by a randomisation technique. *Technometrics*, 8(4), 695-699. doi: 10.2307/1266641
- Efron, B., & Tibshirani, R. J. (1994). *An Introduction to the Bootstrap*. Chapman & Hall/CRC. doi: 10.1201/9780429246593
- Fisher, R. A. (1925). Statistical methods for research workers. Edinburgh: Oliver and Boyd.
- Freedman, D., & Lane, D. (1983). A nonstochastic interpretation of reported significance levels. *Journal of Business and Economic Statistics*, 1(4), 292-298. doi: 10.2307/1391660
- Helwig, N. E. (2019a). Statistical nonparametric mapping: Multivariate permutation tests for location, correlation, and regression problems in neuroimaging. *WIREs Computational Statistics*, 11(2), e1457. doi: 10.1002/wics.1457
- Helwig, N. E. (2019b). Robust nonparametric tests of general linear model coefficients: A comparison of permutation methods and test statistics. *NeuroImage*, 201, 116030. doi: 10.1016/j.neuroimage.2019.116030
- Huh, M.-H., & Jhun, M. (2001). Random permutation testing in multiple linear regression. *Communications in Statistics - Theory and Methods*, 30(10), 2023-2032. doi: 10.1081/STA-100106060
- Janssen, A. (1997). Studentized permutation tests for non-i.i.d. hypotheses and the generalized Behrens-Fisher problem. *Statistics & Probability Letters*, 36 (1), 9-21. doi: 10.1016/S0167-7152(97)00043-6
- Johnson, N. J. (1978). Modified t tests and confidence intervals for asymmetrical populations. *Journal of the American Statistical Association*, 73 (363), 536-544. doi: 10.2307/2286597
- Kennedy, P. E., & Cade, B. S. (1996). Randomization tests for multiple regression. *Communications in Statistics - Simulation and Computation*, 25(4), 923-936. doi: 10.1080/03610919608813350
- Manly, B. (1986). Randomization and regression methods for testing for associations with geographical, environmental and biological distances between populations. *Researches on Population Ecology*, 28(2), 201-218. doi: 10.1007/BF02515450
- Mann, H. B., & Whitney, D. R. (1947). On a test of whether one of two random variables is stochastically larger than the other. *Annals Of Mathematical Statistics*, 18(1), 50-60. doi: 10.1214/aoms/1177730491
- Meyer, D., Dimitriadou, E., Hornik, K., Weingessel, A., & Leisch, F. (2018). e1071: Misc Functions of the Department of Statistics, Probability Theory Group (Formerly: E1071), TU Wien. R package version 1.7-0. <https://CRAN.R-project.org/package=e1071>

- Nichols, T. E., Ridgway, G. R., Webster, M. G., & Smith, S. M. (2008). GLM permutation: non-parametric inference for arbitrary general linear models. *NeuroImage*, 41(S1), S72.
- O'Gorman, T. W. (2005). The performance of randomization tests that use permutations of independent variables. *Communications in Statistics - Simulation and Computation*, 34(4), 895-908. doi: 10.1080/03610910500308230
- Pitman, E. J. G. (1937a). Significance tests which may be applied to samples from any populations. *Supplement to the Journal of the Royal Statistical Society*, 4(1), 119-130. doi: 10.2307/2984124
- Pitman, E. J. G. (1937b). Significance tests which may be applied to samples from any populations. ii. the correlation coefficient test. *Supplement to the Journal of the Royal Statistical Society*, 4(2), 225-232. doi: 10.2307/2983647
- Romano, J. P. (1990). On the behavior of randomization tests without a group invariance assumption. *Journal of the American Statistical Association*, 85(411), 686-692. doi: 10.1080/01621459.1990.10474928
- Still, A. W., & White, A. P. (1981). The approximate randomization test as an alternative to the F test in analysis of variance. *British Journal of Mathematical and Statistical Psychology*, 34(2), 243-252. doi: 10.1111/j.2044-8317.1981.tb00634.x
- Student. (1908). The probable error of a mean. *Biometrika*, 6(1), 1-25. doi: 10.2307/2331554
- ter Braak, C. J. F. (1992). Permutation versus bootstrap significance tests in multiple regression and ANOVA. In K. H. J\"ockel, G. Rothe, & W. Sendler (Eds.), *Bootstrapping and related techniques. lecture notes in economics and mathematical systems*, vol 376 (pp. 79-86). Springer.
- Welch, B. L. (1938). The significance of the difference between two means when the population variances are unequal. *Biometrika*, 39(3/4), 350-362. doi: 10.2307/2332010
- Wilcoxon, F. (1945). Individual comparisons by ranking methods. *Biometrics Bulletin*, 1(6), 80-83. doi: 10.2307/3001968
- White, H. (1980). A heteroscedasticity-consistent covariance matrix and a direct test for heteroscedasticity. *Econometrica*, 48(4), 817-838. doi: 10.2307/1912934
- Winkler, A. M., Ridgway, G. R., Webster, M. A., Smith, S. M., & Nichols, T. E. (2014). Permutation inference for the general linear model. *NeuroImage*, 92, 381-397. doi: 10.1016/j.neuroimage.2014.01.060

Examples

```
# See examples for...
#   flipn      (generate all sign flip vectors)
#   mcse       (Monte Carlo standard errors)
#   np.boot    (nonparametric bootstrap resampling)
#   np.cor.test (nonparametric correlation tests)
#   np.loc.test (nonparametric location tests)
#   np.reg.test (nonparametric regression tests)
#   permn      (generate all permutation vectors)
```

flipn*Generate All Sign-Flips of n Elements*

Description

Generates all 2^n vectors of length n consisting of the elements -1 and 1.

Usage

```
flipn(n)
```

Arguments

n Number of elements.

Details

Adapted from the "bincombinations" function in the [e1071](#) R package.

Value

Matrix of dimension n by 2^n where each column contains a unique sign-flip vector.

Warning

For large n this function will consume a lot of memory and may even crash R.

Note

Used for exact tests in [np.loc.test](#) and [np.reg.test](#).

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

Meyer, D., Dimitriadou, E., Hornik, K., Weingessel, A., & Leisch, F. (2018). e1071: Misc Functions of the Department of Statistics, Probability Theory Group (Formerly: E1071), TU Wien. R package version 1.7-0. <https://CRAN.R-project.org/package=e1071>

Examples

```
flipn(2)  
flipn(3)
```

Description

This function calculates Monte Carlo standard errors for (non-exact) nonparametric tests. The MC-SEs can be used to determine (i) the accuracy of a test for a given number of resamples, or (ii) the number of resamples needed to achieve a test with a given accuracy.

Usage

```
mcse(R, delta, conf.level = 0.95, sig.level = 0.05,
      alternative = c("two.sided", "one.sided"))
```

Arguments

R	Number of resamples (positive integer).
delta	Accuracy of the approximation (number between 0 and 1).
conf.level	Confidence level for the approximation (number between 0 and 1).
sig.level	Significance level of the test (number between 0 and 1).
alternative	Alternative hypothesis (two-sided or one-sided).

Details

Note: either R or delta must be provided.

Let $F(x)$ denote the distribution function for the full permutation distribution, and let $G(x)$ denote the approximation obtained from R resamples. The *Monte Carlo standard error* is given by

$$\sigma(x) = \sqrt{F(x)[1 - F(x)]/R}$$

which is the standard deviation of $G(x)$.

A symmetric confidence interval for $F(x)$ can be approximated as

$$G(x) + / - C\sigma(x)$$

where C is some quantile of the standard normal distribution. Note that the critical value C corresponds to the confidence level (conf.level) of the approximation.

Let α denote the significance level (sig.level) for a one-sided test (α is one-half the significance level for two-sided tests). Define a to be the value of the test statistic such that $F(a) = \alpha$.

The parameter δ (delta) quantifies the accuracy of the approximation, such that

$$|G(a) - \alpha| < \alpha\delta$$

with a given confidence, which is controlled by the conf.level argument.

Value

mcse	Monte Carlo standard error.
R	Number of resamples.
delta	Accuracy of approximation.
conf.level	Confidence level.
sig.level	Significance level.
alternative	Alternative hypothesis.

Note

This function is only relevant for non-exact tests. For exact tests, $F(x) = G(x)$ so the Monte Carlo standard error is zero.

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

Helwig, N. E. (2019). Statistical nonparametric mapping: Multivariate permutation tests for location, correlation, and regression problems in neuroimaging. *WIREs Computational Statistics*, 11(2), e1457. doi: 10.1002/wics.1457

See Also

[np.cor.test](#), [np.loc.test](#), [np.reg.test](#)

Examples

```
##### EXAMPLE 1 #####
# get the Monte Carlo standard error and the
# accuracy (i.e., delta) for given R = 10000
# using the default two-sided alternative hypothesis,
# the default confidence level (conf.level = 0.95),
# and the default significance level (sig.level = 0.05)

mcse(R = 10000)

# se = 0.0016
# delta = 0.1224

##### EXAMPLE 2 #####
# get the Monte Carlo standard error and the
# number of resamples (i.e., R) for given delta = 0.01
# using a one-sided alternative hypothesis,
```

```
# the default confidence level (conf.level = 0.95),
# and the default significance level (sig.level = 0.05)

mcse(delta = 0.1, alternative = "one.sided")

# se = 0.0026
# R = 7299
```

np.boot*Nonparametric Bootstrap Resampling***Description**

Nonparametric bootstrap resampling for univariate and multivariate statistics. Computes bootstrap estimates of the standard error, bias, and covariance. Also computes five different types of bootstrap confidence intervals: normal approximation interval, basic (reverse percentile) interval, percentile interval, studentized (bootstrap-*t*) interval, and bias-corrected and accelerated (BCa) interval.

Usage

```
np.boot(x, statistic, ..., R = 9999, level = c(0.9, 0.95, 0.99),
        method = c("norm", "basic", "perc", "stud", "bca")[-4],
        sdfun = NULL, sdrep = 99, jackknife = NULL,
        parallel = FALSE, cl = NULL, boot.dist = TRUE)
```

Arguments

x	vector of data (for univariate data) or vector of row indices (for multivariate data). See examples for bootstrapping multivariate data.
statistic	function that takes in x (and possibly additional arguments passed using ...) and returns a vector containing the statistic(s). See examples.
...	additional named arguments for the statistic function.
R	number of bootstrap replicates
level	desired confidence level(s) for the computed intervals. Default computes 90%, 95%, and 99% confidence intervals.
method	method(s) for computing confidence intervals. Partial matching is allowed. Any subset of allowable methods is permitted (default computes all intervals except studentized). Set method = NULL to produce no confidence intervals.
sdfun	function for computing the standard deviation of statistic . Should produce a vector the same length as the output of statistic . Only applicable if "stud" %in% method . If NULL , an inner bootstrap is used to estimate the standard deviation.
sdrep	number of bootstrap replicates for the inner bootstrap used to estimate the standard deviation of statistic . Only applicable if "stud" %in% method and sdfun = NULL . Larger values produce more accurate estimates (see Note).

jackknife	function that takes in x (and possibly additional arguments passed using \dots) and returns a vector containing the jackknife statistic(s). Should produce a vector the same length as the output of <code>statistic</code> . Only applicable if "bca" %in% <code>method</code> . If NULL, the <code>jackknife</code> function is defined as the <code>statistic</code> function (default). See the last example for a case when <code>statistic</code> and <code>jackknife</code> are different.
parallel	Logical indicating if the <code>parallel</code> package should be used for parallel computing (of the bootstrap distribution). Defaults to FALSE, which implements sequential computing.
c1	Cluster for parallel computing, which is used when <code>parallel</code> = TRUE. Note that if <code>parallel</code> = TRUE and <code>c1</code> = NULL, then the cluster is defined as <code>makeCluster(2L)</code> to use two cores. To make use of all available cores, use the code <code>c1 = makeCluster(detectCores())</code> .
boot.dist	Logical indicating if the bootstrap distribution should be returned (see Note).

Details

The first three intervals (normal, basic, and percentile) are only first-order accurate, whereas the last two intervals (studentized and BCa) are both second-order accurate. Thus, the results from the studentized and BCa intervals tend to provide more accurate coverage rates.

Unless the standard deviation function for the studentized interval is input via the `sdfun` argument, the studentized interval can be quite computationally costly. This is because an inner bootstrap is needed to estimate the standard deviation of the statistic for each (outer) bootstrap replicate—and you may want to increase the default number of inner bootstrap replicates (see Note).

The efficiency of the BCa interval will depend on the sample size n and the computational complexity of the (jackknife) statistic estimate. Assuming that n is not too large and the jackknife statistic is not too difficult to compute, the BCa interval can be computed reasonably quickly—especially in comparison the studentized interval with an inner bootstrap.

Computational details of the various confidence intervals are described in Efron and Tibshirani (1994) and in Davison and Hinkley (1997). For a useful and concise discussion of the various intervals, see Carpenter and Bithell (2000).

Value

t0	Observed statistic, computed using <code>statistic(x, ...)</code>
se	Bootstrap estimate of the standard error.
bias	Bootstrap estimate of the bias.
cov	Bootstrap estimate of the covariance (for multivariate statistics).
normal	Normal approximation confidence interval(s).
basic	Basic (reverse percentile) confidence interval(s).
percent	Percentile confidence interval(s).
student	Studentized (bootstrap- t) confidence interval(s).
bca	Bias-corrected and accelerated (BCa) confidence interval(s).
z0	Bias-correction factor(s). Only provided if <code>bca %in% method</code> .
acc	Acceleration factor(s). Only provided if <code>bca %in% method</code> .

<code>boot.dist</code>	Bootstrap distribution of statistic(s). Only provided if <code>boot.dist = TRUE</code> .
<code>R</code>	Number of bootstrap replicates (same as input).
<code>level</code>	Confidence level (same as input).
<code>sdfun</code>	Standard deviation function for statistic (same as input).
<code>sdrep</code>	Number of inner bootstrap replicates (same as input).
<code>jackknife</code>	Jackknife function (same as input).

Note

If `boot.dist = TRUE`, the output `boot.dist` will be a matrix of dimension `R` by `length(statistic(x, ...))` if the statistic is multivariate. Otherwise the bootstrap distribution will be a vector of length `R`.

For the "stud" method, the default of `sdrep = 99` may produce a crude estimate of the standard deviation of the statistic(s). For more accurate estimates, the value of `sdrep` may need to be set substantially larger, e.g., `sdrep = 999`.

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

- Carpenter, J., & Bithell, J. (2000). Bootstrap confidence intervals: when, which, what? A practical guide for medical statisticians. *Statistics in Medicine*, 19(9), 1141-1164. doi: 10.1002/(SICI)1097-0258(20000515)19:9%3C1141::AID-SIM479%3E3.0.CO;2-F
- Davison, A. C., & Hinkley, D. V. (1997). *Bootstrap Methods and Their Application*. Cambridge University Press. doi: 10.1017/CBO9780511802843
- Efron, B., & Tibshirani, R. J. (1994). *An Introduction to the Bootstrap*. Chapman & Hall/CRC. doi: 10.1201/9780429246593

Examples

```
#####*****#####
      UNIVARIATE DATA      #####
#####*****#####

### Example 1: univariate statistic (median)

# generate 100 standard normal observations
set.seed(1)
n <- 100
x <- rnorm(n)

# nonparametric bootstrap
npbs <- np.boot(x = x, statistic = median)
npbs

### Example 2: multivariate statistic (quartiles)
```

```

# generate 100 standard normal observations
set.seed(1)
n <- 100
x <- rnorm(n)

# nonparametric bootstrap
npbs <- np.boot(x = x, statistic = quantile,
                  probs = c(0.25, 0.5, 0.75))
npbs

#####
##### MULTIVARIATE DATA #####
#####

### Example 1: univariate statistic (correlation)

# correlation matrix square root (with rho = 0.5)
rho <- 0.5
val <- c(sqrt(1 + rho), sqrt(1 - rho))
corsqrt <- matrix(c(val[1], -val[2], val), 2, 2) / sqrt(2)

# generate 100 bivariate observations (with rho = 0.5)
n <- 100
set.seed(1)
data <- cbind(rnorm(n), rnorm(n)) %*% corsqrt

# define statistic function
statfun <- function(x, data) cor(data[x,1], data[x,2])

# nonparametric bootstrap
npbs <- np.boot(x = 1:n, statistic = statfun, data = data)
npbs

### Example 2: multivariate statistic (variances and covariance)

# correlation matrix square root (with rho = 0.5)
rho <- 0.5
val <- c(sqrt(1 + rho), sqrt(1 - rho))
corsqrt <- matrix(c(val[1], -val[2], val), 2, 2) / sqrt(2)

# generate 100 bivariate observations (with rho = 0.5)
n <- 100
set.seed(1)
data <- cbind(rnorm(n), rnorm(n)) %*% corsqrt

# define statistic function
statfun <- function(x, data) {
  cmat <- cov(data[x,])
  ltri <- lower.tri(cmat, diag = TRUE)
  cvec <- cmat[ltri]
  names(cvec) <- c("var(x1)", "cov(x1,x2)", "var(x2)")
  cvec
}

```

```

}

# nonparametric bootstrap
npbs <- np.boot(x = 1:n, statistic = statfun, data = data)
npbs

## Not run:

#####*****#####
## Example 1: bootstrap cases

# generate 100 observations
n <- 100
set.seed(1)
x <- seq(0, 1, length.out = n)
y <- 1 + 2 * x + rnorm(n)
data <- data.frame(x = x, y = y)

# define statistic function
statfun <- function(x, data) {
  xmat <- cbind(1, data$x[x])
  xinv <- solve(crossprod(xmat)) %*% t(xmat)
  coef <- as.numeric(xinv %*% data$y[x])
  names(coef) <- c("(Intercept)", "x")
  coef
}

# nonparametric bootstrap
npbs <- np.boot(x = 1:n, statistic = statfun, data = data)
npbs

## Example 2: bootstrap residuals

# generate 100 observations
n <- 100
set.seed(1)
x <- seq(0, 1, length.out = n)
y <- 1 + 2 * x + rnorm(n)

# prepare data
xmat <- cbind(1, x)
xinv <- solve(crossprod(xmat)) %*% t(xmat)
fit <- xmat %*% xinv %*% y
data <- list(fit = fit, resid = y - fit, xinv = xinv, x = x)

# define statistic function
statfun <- function(x, data) {
  ynew <- data$fit + data$resid[x]
  coef <- as.numeric(data$xinv %*% ynew)
}

```

```

names(coef) <- c("(Intercept)", "x")
coef
}

# define jackknife function
jackfun <- function(x, data){
  ynew <- data$fit[x] + data$resid[x]
  xmat <- cbind(1, data$x[x])
  xinv <- solve(crossprod(xmat)) %*% t(xmat)
  coef <- as.numeric(xinv %*% ynew)
  names(coef) <- c("(Intercept)", "x")
  coef
}

# nonparametric bootstrap
npbs <- np.boot(x = 1:n, statistic = statfun, data = data,
                 jackknife = jackfun)
npbs

## End(Not run)

```

np.cor.test*Nonparametric Tests of Correlation Coefficients***Description**

Denoting the Pearson product-moment correlation coefficient as

$$\rho = \text{Cov}(X, Y) / \sqrt{\text{Var}(X)\text{Var}(Y)}$$

this function implements permutation tests of $H_0 : \rho = \rho_0$ where ρ_0 is the user-specified null value. Can also implement tests of partial correlations, semi-partial (or part) correlations, and independence.

Usage

```
np.cor.test(x, y, z = NULL,
            alternative = c("two.sided", "less", "greater"),
            rho = 0, independent = FALSE, partial = TRUE,
            R = 9999, parallel = FALSE, cl = NULL,
            perm.dist = TRUE, na.rm = TRUE)
```

Arguments

- x** X vector (n by 1).
- y** Y vector (n by 1).
- z** Optional Z matrix (n by q). If provided, the partial (or semi-partial if **partial** = FALSE) correlation is calculated between x and y controlling for z.

<code>alternative</code>	Alternative hypothesis. Must be either "two.sided" ($H_1 : \rho \neq \rho_0$), "less" ($H_1 : \rho < \rho_0$), or "greater" ($H_1 : \rho > \rho_0$).
<code>rho</code>	Null hypothesis value ρ_0 . Defaults to zero.
<code>independent</code>	If FALSE (default), the null hypothesis is $H_0 : \rho = \rho_0$. Otherwise, the null hypothesis is that X and Y are independent, i.e., $H_0 : F_{XY}(x, y) = F_X(x)F_Y(y)$.
<code>partial</code>	Only applicable if z is provided. If TRUE (default), the partial correlation between x and y controlling for z is tested. Otherwise the semi-partial correlation is tested. See Details.
<code>R</code>	Number of resamples for the permutation test (positive integer).
<code>parallel</code>	Logical indicating if the <code>parallel</code> package should be used for parallel computing (of the permutation distribution). Defaults to FALSE, which implements sequential computing.
<code>c1</code>	Cluster for parallel computing, which is used when <code>parallel</code> = TRUE. Note that if <code>parallel</code> = TRUE and <code>c1</code> = NULL, then the cluster is defined as <code>makeCluster(2L)</code> to use two cores. To make use of all available cores, use the code <code>c1 = makeCluster(detectCores())</code> .
<code>perm.dist</code>	Logical indicating if the permutation distribution should be returned.
<code>na.rm</code>	If TRUE (default), the arguments x and y (and z if provided) are passed to the <code>na.omit</code> function to remove cases with missing data.

Details

Default use of this function tests the Pearson correlation between X and Y using the studentized test statistic proposed by DiCiccio and Romano (2017). If `independent` = TRUE, the classic (unstudentized) test statistic is used to test the null hypothesis of independence.

If Z is provided, the partial or semi-partial correlation between X and Y controlling for Z is tested. For the semi-partial correlation, the effect of Z is partialled out of X .

Value

<code>statistic</code>	Test statistic value.
<code>p.value</code>	p-value for testing $H_0 : \rho = \rho_0$ or $H_0 : F_{XY}(x, y) = F_X(x)F_Y(y)$.
<code>perm.dist</code>	Permutation distribution of <code>statistic</code> .
<code>alternative</code>	Alternative hypothesis.
<code>null.value</code>	Null hypothesis value for ρ .
<code>independent</code>	Independence test?
<code>R</code>	Number of resamples.
<code>exact</code>	Exact permutation test? See Note.
<code>estimate</code>	Sample estimate of correlation coefficient ρ .

Note

The permutation test will be exact when the requested number of resamples R is greater than factorial(n) minus one. In this case, the permutation distribution perm.dist contains all factorial(n) possible values of the test statistic.

If z = NULL, the result will be the same as using [np.reg.test](#) with method = "perm".

If z is supplied and partial = TRUE, the result will be the same as using [np.reg.test](#) with method = "KC" and homosced = FALSE.

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

- DiCiccio, C. J., & Romano, J. P. (2017). Robust permutation tests for correlation and regression coefficients. *Journal of the American Statistical Association*, 112(519), 1211-1220. doi: 10.1080/01621459.2016.1202117
- Helwig, N. E. (2019). Statistical nonparametric mapping: Multivariate permutation tests for location, correlation, and regression problems in neuroimaging. *WIREs Computational Statistics*, 11(2), e1457. doi: 10.1002/wics.1457
- Pitman, E. J. G. (1937b). Significance tests which may be applied to samples from any populations. ii. the correlation coefficient test. *Supplement to the Journal of the Royal Statistical Society*, 4(2), 225-232. doi: 10.2307/2983647

See Also

[plot.np.cor.test](#) S3 plotting method for visualizing the results

Examples

```
# generate data
rho <- 0.5
val <- c(sqrt(1 + rho), sqrt(1 - rho))
corsqrt <- matrix(c(val[1], -val[2], val), 2, 2) / sqrt(2)
set.seed(1)
n <- 10
z <- cbind(rnorm(n), rnorm(n)) %*% corsqrt
x <- z[,1]
y <- z[,2]

# test H0: rho = 0
set.seed(0)
np.cor.test(x, y)

# test H0: X and Y are independent
set.seed(0)
np.cor.test(x, y, independent = TRUE)
```

`np.loc.test`*Nonparametric Tests of Location Parameters*

Description

Performs one and two sample nonparametric (randomization) tests of location parameters, i.e., means and medians. Implements univariate and multivariate tests using eight different test statistics: Student's one-sample t-test, Johnson's modified t-test, Wilcoxon's Signed Rank test, Fisher's Sign test, Student's two-sample t-test, Welch's t-test, Wilcoxon's Rank Sum test (i.e., Mann-Whitney's U test), and a studentized Wilcoxon test for unequal variances.

Usage

```
np.loc.test(x, y = NULL,
            alternative = c("two.sided", "less", "greater"),
            mu = 0, paired = FALSE, var.equal = FALSE,
            median.test = FALSE, symmetric = TRUE,
            R = 9999, parallel = FALSE, cl = NULL,
            perm.dist = TRUE, na.rm = TRUE)
```

Arguments

<code>x</code>	Numeric vector (or matrix) of data values.
<code>y</code>	Optional numeric vector (or matrix) of data values.
<code>alternative</code>	Alternative hypothesis. Must be either "two.sided" ($H_1 : \mu \neq \mu_0$), "less" ($H_1 : \mu < \mu_0$), or "greater" ($H_1 : \mu > \mu_0$).
<code>mu</code>	Null hypothesis value μ_0 . Defaults to zero.
<code>paired</code>	Logical indicating whether you want a paired location test.
<code>var.equal</code>	Logical indicating whether to treat the two variances as being equal.
<code>median.test</code>	Logical indicating whether the location test is for the median. Default is FALSE, i.e., μ is the mean.
<code>symmetric</code>	Logical indicating if the distribution of <code>x</code> should be assumed to be symmetric around μ . Only used for one (or paired) sample tests.
<code>R</code>	Number of resamples for the permutation test (positive integer).
<code>parallel</code>	Logical indicating if the <code>parallel</code> package should be used for parallel computing (of the permutation distribution). Defaults to FALSE, which implements sequential computing.
<code>cl</code>	Cluster for parallel computing, which is used when <code>parallel</code> = TRUE. Note that if <code>parallel</code> = TRUE and <code>cl</code> = NULL, then the cluster is defined as <code>makeCluster(2L)</code> to use two cores. To make use of all available cores, use the code <code>cl = makeCluster(detectCores())</code> .
<code>perm.dist</code>	Logical indicating if the permutation distribution should be returned.
<code>na.rm</code>	If TRUE (default), the arguments <code>x</code> (and <code>y</code> if provided) are passed to the <code>na.omit</code> function to remove cases with missing data.

Details

One sample	μ is the mean (or median) of X
Paired	μ is the mean (or median) of $X - Y$
Two sample	μ is the mean difference $E(X) - E(Y)$ or the median of the differences $X - Y$

For one (or paired) sample tests, the different test statistics can be obtained using

median.test = F	median.test = T
symmetric = F	Johnson t test
symmetric = T	Fisher sign test Student t test

Wilcoxon signed rank test

For two sample tests, the different test statistics can be obtained using

median.test = F	median.test = T
var.equal = F	Welch t test
var.equal = T	Student t test

Wilcoxon rank sum test

Value

statistic	Test statistic value.
p.value	p-value for testing $H_0 : \mu = \mu_0$.
perm.dist	Permutation distribution of statistic.
alternative	Alternative hypothesis.
null.value	Null hypothesis value for μ .
var.equal	Assuming equal variances? Only for two sample tests.
median.test	Testing the median?
symmetric	Assuming symmetry? Only for one sample and paired tests.
R	Number of resamples.
exact	Exact permutation test? See Note.
estimate	Estimate of parameter μ .
univariate	Univariate test statistic value for j -th variable (for multivariate input).
adj.p.value	Adjusted p-value for testing significance of j -th variable (for multivariate input).
method	Method used for permutation test. See Details.

Multivariate Tests

If the input x (and possibly y) is a matrix with $m > 1$ columns, the multivariate test statistic is defined as

alternative	statistic
two.sided	$\max(\text{abs}(\text{univariate}))$
less	$\min(\text{univariate})$
greater	$\max(\text{univariate})$

The global null hypothesis (across all m variables) is tested by comparing the observed statistic to the permutation distribution `perm.dist`. This produces the `p.value` for testing the global null hypothesis.

The local null hypothesis (separately for each variable) is tested by comparing the univariate test statistic to `perm.dist`. This produces the adjusted p-values (`adj.p.values`), which control the familywise Type I error rate across the m tests.

Note

For one sample (or paired) tests, the permutation test will be exact when the requested number of resamples R is greater than 2^n minus one. In this case, the permutation distribution `perm.dist` contains all 2^n possible values of the test statistic.

For two sample tests, the permutation test will be exact when the requested number of resamples R is greater than `choose(N, n)` minus one, where $m = \text{length}(x)$, $n = \text{length}(y)$, and $N = m + n$. In this case, the permutation distribution `perm.dist` contains all `choose(N, n)` possible values of the test statistic.

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

- Blair, R. C., Higgins, J. J., Karniski, W., & Kromrey, J. D. (1994). A study of multivariate permutation tests which may replace Hotelling's T₂ test in prescribed circumstances. *Multivariate Behavioral Research*, 29(2), 141-163. doi: 10.1207/s15327906mbr2902_2
- Chung, E., & Romano, J. P. (2016). Asymptotically valid and exact permutation tests based on two-sample U-statistics. *Journal of Statistical Planning and Inference*, 168, 97-105. doi: 10.1016/j.jspi.2015.07.004
- Fisher, R. A. (1925). *Statistical methods for research workers*. Edinburgh: Oliver and Boyd.
- Helwig, N. E. (2019). Statistical nonparametric mapping: Multivariate permutation tests for location, correlation, and regression problems in neuroimaging. *WIREs Computational Statistics*, 11(2), e1457. doi: 10.1002/wics.1457
- Janssen, A. (1997). Studentized permutation tests for non-i.i.d. hypotheses and the generalized Behrens-Fisher problem. *Statistics & Probability Letters*, 36 (1), 9-21. doi: 10.1016/S0167-7152(97)00043-6
- Johnson, N. J. (1978). Modified t tests and confidence intervals for asymmetrical populations. *Journal of the American Statistical Association*, 73 (363), 536-544. doi: 10.2307/2286597
- Mann, H. B., & Whitney, D. R. (1947). On a test of whether one of two random variables is stochastically larger than the other. *Annals Of Mathematical Statistics*, 18(1), 50-60. doi: 10.1214/aoms/1177730491
- Pitman, E. J. G. (1937a). Significance tests which may be applied to samples from any populations. *Supplement to the Journal of the Royal Statistical Society*, 4(1), 119-130. doi: 10.2307/2984124
- Romano, J. P. (1990). On the behavior of randomization tests without a group invariance assumption. *Journal of the American Statistical Association*, 85(411), 686-692. doi: 10.1080/01621459.1990.10474928
- Student. (1908). The probable error of a mean. *Biometrika*, 6(1), 1-25. doi: 10.2307/2331554
- Welch, B. L. (1938). The significance of the difference between two means when the population variances are unequal. *Biometrika*, 39(3/4), 350-362. doi: 10.2307/2332010

Wilcoxon, F. (1945). Individual comparisons by ranking methods. Biometrics Bulletin, 1(6), 80-83.
doi: 10.2307/3001968

See Also

[plot.np.loc.test](#) S3 plotting method for visualizing the results

Examples

```
#####*****##### UNIVARIATE #####*****#####
#####***## ONE SAMPLE ####*##*##*##

# generate data
set.seed(1)
n <- 10
x <- rnorm(n, mean = 0.5)

# one sample t-test
set.seed(0)
np.loc.test(x)

# Johnson t-test
set.seed(0)
np.loc.test(x, symmetric = FALSE)

# Wilcoxon signed rank test
set.seed(0)
np.loc.test(x, median.test = TRUE)

# Fisher sign test
set.seed(0)
np.loc.test(x, median.test = TRUE, symmetric = FALSE)

#####***## PAIRED SAMPLE ####*##*##*##

# generate data
set.seed(1)
n <- 10
x <- rnorm(n, mean = 0.5)
y <- rnorm(n)

# paired t-test
set.seed(0)
np.loc.test(x, y, paired = TRUE)

# paired Johnson t-test
set.seed(0)
np.loc.test(x, y, paired = TRUE, symmetric = FALSE)

# paired Wilcoxon signed rank test
```

```
set.seed(0)
np.loc.test(x, y, paired = TRUE, median.test = TRUE)

# paired Fisher sign test
set.seed(0)
np.loc.test(x, y, paired = TRUE, median.test = TRUE, symmetric = FALSE)

#####***## TWO SAMPLE #######***##

# generate data
set.seed(1)
m <- 7
n <- 8
x <- rnorm(m, mean = 0.5)
y <- rnorm(n)

# Welch t-test
set.seed(0)
np.loc.test(x, y)

# Student t-test
set.seed(0)
np.loc.test(x, y, var.equal = TRUE)

# Studentized Wilcoxon test
set.seed(0)
np.loc.test(x, y, median.test = TRUE)

# Wilcoxon rank sum test
set.seed(0)
np.loc.test(x, y, var.equal = TRUE, median.test = TRUE)

## Not run:

#####*****##### MULTIVARIATE #####*****#####

#####***## ONE SAMPLE #######***##

# generate data
set.seed(1)
n <- 10
x <- cbind(rnorm(n, mean = 0.5),
            rnorm(n, mean = 1),
            rnorm(n, mean = 1.5))

# multivariate one sample t-test
set.seed(0)
ptest <- np.loc.test(x)
ptest
ptest$univariate
```

```

ptest$adj.p.values

#####***## PAIRED SAMPLE #####***##

# generate data
set.seed(1)
n <- 10
x <- cbind(rnorm(n, mean = 0.5),
            rnorm(n, mean = 1),
            rnorm(n, mean = 1.5))
y <- matrix(rnorm(n * 3), nrow = n, ncol = 3)

# multivariate paired t-test
set.seed(0)
ptest <- np.loc.test(x, y, paired = TRUE)
ptest
ptest$univariate
ptest$adj.p.values

#####***## TWO SAMPLE #####***##

# generate data
set.seed(1)
m <- 7
n <- 8
x <- cbind(rnorm(m, mean = 0.5),
            rnorm(m, mean = 1),
            rnorm(m, mean = 1.5))
y <- matrix(rnorm(n * 3), nrow = n, ncol = 3)

# multivariate Welch t-test
set.seed(0)
ptest <- np.loc.test(x, y)
ptest
ptest$univariate
ptest$adj.p.values

## End(Not run)

```

Description

Assuming a linear model of the form

$$Y = \alpha + X\beta + \epsilon$$

or

$$Y = \alpha + X\beta + Z\gamma + \epsilon$$

this function implements permutation tests of $H_0 : \beta = \beta_0$ where β_0 is the user-specified null vector.

Usage

```
np.reg.test(x, y, z = NULL, method = NULL,
            beta = NULL, homosced = FALSE, lambda = 0,
            R = 9999, parallel = FALSE, cl = NULL,
            perm.dist = TRUE, na.rm = TRUE)
```

Arguments

x	Matrix of predictor variables (n by p).
y	Response vector or matrix (n by m).
z	Optional matrix of nuisance variables (n by q).
method	Permutation method. See Details.
beta	Null hypothesis value for β (p by m). Defaults to matrix of zeros.
homosced	Are the ϵ terms homoscedastic? If FALSE (default), a robust Wald test statistic is used. Otherwise the classic F test statistic is used.
lambda	Scalar or vector of ridge parameter(s). Defaults to vector of zeros.
R	Number of resamples for the permutation test (positive integer).
parallel	Logical indicating if the <code>parallel</code> package should be used for parallel computing (of the permutation distribution). Defaults to FALSE, which implements sequential computing.
cl	Cluster for parallel computing, which is used when <code>parallel</code> = TRUE. Note that if <code>parallel</code> = TRUE and <code>cl</code> = NULL, then the cluster is defined as <code>makeCluster(2L)</code> to use two cores. To make use of all available cores, use the code <code>cl = makeCluster(detectCores())</code> .
perm.dist	Logical indicating if the permutation distribution should be returned.
na.rm	If TRUE (default), the arguments x and y (and z if provided) are passed to the <code>na.omit</code> function to remove cases with missing data.

Details

With no nuisance variables in the model (i.e., `z` = `NULL`), there are three possible options for the `method` argument:

Method	Model
perm	$PY = \alpha + X\beta + \epsilon$
flip	$SY = \alpha + X\beta + \epsilon$
both	$PSY = \alpha + X\beta + \epsilon$

where P is a permutation matrix and S is a sign-flipping matrix.

With nuisance variables in the model, there are eight possible options for the `method` argument:

Method	Name	Model
HJ	Huh-Jhun	$PQ'R_zY = \alpha + Q'R_zX\beta + \epsilon$
KC	Kennedy-Cade	$PR_zY = \alpha + R_zX\beta + \epsilon$
SW	Still-White	$PR_zY = \alpha + X\beta + \epsilon$
TB	ter Braak	$(PR_m + H_m)Y = \alpha + X\beta + Z\gamma + \epsilon$
FL	Freedman-Lane	$(PR_z + H_z)Y = \alpha + X\beta + Z\gamma + \epsilon$
MA	Manly	$PY = \alpha + X\beta + Z\gamma + \epsilon$
OS	O'Gorman-Smith	$Y = \alpha + PR_zX\beta + Z\gamma + \epsilon$
DS	Draper-Stoneman	$Y = \alpha + PX\beta + Z\gamma + \epsilon$

where P is permutation matrix and Q is defined as $R_z = QQ'$ with $Q'Q = I$.

Note that H_z is the hat matrix for the nuisance variable design matrix, and $R_z = I - H_z$ is the corresponding residual forming matrix. Similarly, H_m and R_m are the hat and residual forming matrices for the full model including the predictor and nuisance variables.

Value

statistic	Test statistic value.
p.value	p-value for testing $H_0 : \beta = \beta_0$.
perm.dist	Permutation distribution of statistic.
method	Permutation method.
null.value	Null hypothesis value for β .
homosced	Homoscedastic errors?
R	Number of resamples.
exact	Exact permutation test? See Note.
coefficients	Least squares estimates of α , β , and γ (if applicable).
univariate	Univariate test statistic value for j -th variable (for multivariate inputs).
adj.p.value	Adjusted p-value for testing significance of j -th variable (for multivariate inputs).

Multivariate Tests

If the input y is a matrix with $m > 1$ columns, the multivariate test statistic is defined as `statistic = max(univariate)` given that the univariate test statistics are non-negative.

The global null hypothesis (across all m variables) is tested by comparing the observed `statistic` to the permutation distribution `perm.dist`. This produces the `p.value` for testing the global null hypothesis.

The local null hypothesis (separately for each variable) is tested by comparing the `univariate` test statistic to `perm.dist`. This produces the adjusted p-values (`adj.p.values`), which control the familywise Type I error rate across the m tests.

Note

If `method = "flip"`, the permutation test will be exact when the requested number of resamples `R` is greater than 2^n minus one. In this case, the permutation distribution `perm.dist` contains all 2^n possible values of the test statistic.

If `method = "both"`, the permutation test will be exact when the requested number of resamples `R` is greater than `factorial(n) * (2^n)` minus one. In this case, the permutation distribution `perm.dist` contains all `factorial(n) * (2^n)` possible values of the test statistic.

If `method = "HJ"`, the permutation test will be exact when the requested number of resamples `R` is greater than `factorial(n-q-1)` minus one. In this case, the permutation distribution `perm.dist` contains all `factorial(n-q-1)` possible values of the test statistic.

Otherwise the permutation test will be exact when the requested number of resamples `R` is greater than `factorial(n)` minus one. In this case, the permutation distribution `perm.dist` contains all `factorial(n)` possible values of the test statistic.

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

- DiCiccio, C. J., & Romano, J. P. (2017). Robust permutation tests for correlation and regression coefficients. *Journal of the American Statistical Association*, 112(519), 1211-1220. doi: 10.1080/01621459.2016.1202117
- Draper, N. R., & Stoneman, D. M. (1966). Testing for the inclusion of variables in linear regression by a randomisation technique. *Technometrics*, 8(4), 695-699. doi: 10.2307/1266641
- Freedman, D., & Lane, D. (1983). A nonstochastic interpretation of reported significance levels. *Journal of Business and Economic Statistics*, 1(4), 292-298. doi: 10.2307/1391660
- Helwig, N. E. (2019a). Statistical nonparametric mapping: Multivariate permutation tests for location, correlation, and regression problems in neuroimaging. *WIREs Computational Statistics*, 11(2), e1457. doi: 10.1002/wics.1457
- Helwig, N. E. (2019b). Robust nonparametric tests of general linear model coefficients: A comparison of permutation methods and test statistics. *NeuroImage*, 201, 116030. doi: 10.1016/j.neuroimage.2019.116030
- Huh, M.-H., & Jhun, M. (2001). Random permutation testing in multiple linear regression. *Communications in Statistics - Theory and Methods*, 30(10), 2023-2032. doi: 10.1081/STA-100106060
- Kennedy, P. E., & Cade, B. S. (1996). Randomization tests for multiple regression. *Communications in Statistics - Simulation and Computation*, 25(4), 923-936. doi: 10.1080/03610919608813350
- Manly, B. (1986). Randomization and regression methods for testing for associations with geographical, environmental and biological distances between populations. *Researches on Population Ecology*, 28(2), 201-218. doi: 10.1007/BF02515450
- Nichols, T. E., Ridgway, G. R., Webster, M. G., & Smith, S. M. (2008). GLM permutation: nonparametric inference for arbitrary general linear models. *NeuroImage*, 41(S1), S72.
- O'Gorman, T. W. (2005). The performance of randomization tests that use permutations of independent variables. *Communications in Statistics - Simulation and Computation*, 34(4), 895-908. doi: 10.1080/03610910500308230

- Still, A. W., & White, A. P. (1981). The approximate randomization test as an alternative to the F test in analysis of variance. *British Journal of Mathematical and Statistical Psychology*, 34(2), 243-252. doi: 10.1111/j.2044-8317.1981.tb00634.x
- ter Braak, C. J. F. (1992). Permutation versus bootstrap significance tests in multiple regression and ANOVA. In K. H. J\"ockel, G. Rothe, & W. Sendler (Eds.), *Bootstrapping and related techniques. lecture notes in economics and mathematical systems*, vol 376 (pp. 79-86). Springer.
- White, H. (1980). A heteroscedasticity-consistent covariance matrix and a direct test for heteroscedasticity. *Econometrica*, 48(4), 817-838. doi: 10.2307/1912934
- Winkler, A. M., Ridgway, G. R., Webster, M. A., Smith, S. M., & Nichols, T. E. (2014). Permutation inference for the general linear model. *NeuroImage*, 92, 381-397. doi: 10.1016/j.neuroimage.2014.01.060

See Also

[plot.np.reg.test](#) S3 plotting method for visualizing the results

Examples

```
#####*****#####
      UNIVARIATE      ######*****#####

#####***#####
      TEST ALL COEFFICIENTS      #####***#####

# generate data
set.seed(1)
n <- 10
x <- cbind(rnorm(n), rnorm(n))
y <- rnorm(n)

# Wald test (method = "perm")
set.seed(0)
np.reg.test(x, y)

# F test (method = "perm")
set.seed(0)
np.reg.test(x, y, homosced = TRUE)

#####***#####
      TEST SUBSET OF COEFFICIENTS      #####***#####

# generate data
set.seed(1)
n <- 10
x <- rnorm(n)
z <- rnorm(n)
y <- 3 + 2 * z + rnorm(n)

# Wald test (method = "HJ")
set.seed(0)
np.reg.test(x, y, z)

# F test (method = "HJ")
```

```

set.seed(0)
np.reg.test(x, y, z, homosced = TRUE)

## Not run:

#####*****#####  MULTIVARIATE  ######*****#####

#####***##  TEST ALL COEFFICIENTS  #####***##

# generate data
set.seed(1)
n <- 10
x <- cbind(rnorm(n), rnorm(n))
y <- matrix(rnorm(n * 3), nrow = n, ncol = 3)

# multivariate Wald test (method = "perm")
set.seed(0)
np.reg.test(x, y)

# multivariate F test (method = "perm")
set.seed(0)
np.reg.test(x, y, homosced = TRUE)

#####***##  TEST SUBSET OF COEFFICIENTS  #####***##

# generate data
set.seed(1)
n <- 10
x <- rnorm(n)
z <- rnorm(n)
y <- cbind(1 + 3 * z + rnorm(n),
           2 + 2 * z + rnorm(n),
           3 + 1 * z + rnorm(n))

# multivariate Wald test (method = "HJ")
set.seed(0)
np.reg.test(x, y, z)

# multivariate F test (method = "HJ")
set.seed(0)
np.reg.test(x, y, z, homosced = TRUE)

## End(Not run)

```

Description

Generates all $n!$ vectors of length n consisting of permutations of the integers 1 to n .

Usage

```
permn(n)
```

Arguments

n	Number of elements.
---	---------------------

Details

Adapted from the "permutations" function in the [e1071](#) R package.

Value

Matrix of dimension n by $n!$ where each column contains a unique permutation vector.

Warning

For large n this function will consume a lot of memory and may even crash R.

Note

Used for exact tests in [np.cor.test](#) and [np.reg.test](#).

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

Meyer, D., Dimitriadou, E., Hornik, K., Weingessel, A., & Leisch, F. (2018). e1071: Misc Functions of the Department of Statistics, Probability Theory Group (Formerly: E1071), TU Wien. R package version 1.7-0. <https://CRAN.R-project.org/package=e1071>

Examples

```
permn(2)
permn(3)
```

plot	<i>Plots Permutation Distribution for Nonparametric Tests</i>
-------------	---

Description

plot methods for object classes "np.cor.test", "np.loc.test", and "np.reg.test"

Usage

```
## S3 method for class 'np.cor.test'
plot(x, alpha = 0.05, col = "grey", col.rr = "red",
      col.stat = "black", lty.stat = 2, lwd.stat = 2,
      xlab = "Test Statistic", main = "Permutation Distribution",
      breaks = "scott", border = NA, box = TRUE, ...)

## S3 method for class 'np.loc.test'
plot(x, alpha = 0.05, col = "grey", col.rr = "red",
      col.stat = "black", lty.stat = 2, lwd.stat = 2,
      xlab = "Test Statistic", main = "Permutation Distribution",
      breaks = "scott", border = NA, box = TRUE, ...)

## S3 method for class 'np.reg.test'
plot(x, alpha = 0.05, col = "grey", col.rr = "red",
      col.stat = "black", lty.stat = 2, lwd.stat = 2,
      xlab = "Test Statistic", main = "Permutation Distribution",
      breaks = "scott", border = NA, box = TRUE, SQRT = TRUE, ...)
```

Arguments

x	an object of class "np.cor.test" output by the np.cor.test function, "np.loc.test" output by the np.loc.test function, or "np.reg.test" output by the np.reg.test function
alpha	significance level of the nonparametric test
col	color for plotting the non-rejection region
col.rr	color for plotting the rejection region
col.stat	color for plotting the observed test statistic
lty.stat	line type for plotting the observed test statistic
lwd.stat	line width for plotting the observed test statistic
xlab	x-axis label for the plot
main	title for the plot
breaks	defines the breaks of the histogram (see hist)
border	color of the border around the bars
box	should a box be drawn around the plot?

SQRT for regression tests, should the permutation distribution (and test statistic) be plotted on the square-root scale?
 ... additional arguments to be passed to [hist](#)

Details

Plots a histogram of the permutation distribution and the observed test statistic. The argument 'alpha' controls the rejection region of the nonparametric test, which is plotted using a separate color (default is red).

Author(s)

Nathaniel E. Helwig <helwig@umn.edu>

References

Helwig, N. E. (2019). Statistical nonparametric mapping: Multivariate permutation tests for location, correlation, and regression problems in neuroimaging. *WIREs Computational Statistics*, 11(2), e1457. doi: 10.1002/wics.1457

See Also

[np.cor.test](#) for information on nonparametric correlation tests
[np.loc.test](#) for information on nonparametric location tests
[np.reg.test](#) for information on nonparametric regression tests

Examples

```
#####*****#####
  np.cor.test  ######*****#####

# generate data
rho <- 0.5
val <- c(sqrt(1 + rho), sqrt(1 - rho))
corsqrt <- matrix(c(val[1], -val[2], val), 2, 2) / sqrt(2)
set.seed(1)
n <- 50
z <- cbind(rnorm(n), rnorm(n)) %*% corsqrt
x <- z[,1]
y <- z[,2]

# test H0: rho = 0
set.seed(0)
test <- np.cor.test(x, y)

# plot results
plot(test)

#####*****#####
  np.loc.test  ######*****#####
```

```
# generate data
set.seed(1)
n <- 50
x <- rnorm(n, mean = 0.5)

# one sample t-test
set.seed(0)
test <- np.loc.test(x)

# plot results
plot(test)

#####*****#####
np.reg.test #####
#####*****#####

# generate data
set.seed(1)
n <- 50
x <- cbind(rnorm(n), rnorm(n))
beta <- c(0.25, 0.5)
y <- x %*% beta + rnorm(n)

# Wald test (method = "perm")
set.seed(0)
test <- np.reg.test(x, y)

# plot results
plot(test)
```

StartupMessage

Startup Message for nptest

Description

Prints the startup message when nptest is loaded. Not intended to be called by the user.

Details

The ‘nptest’ ascii start-up message was created using the taag software.

References

<https://patorjk.com/software/taag/>

Index

- * **aplot**
 - plot, 29
- * **dplot**
 - plot, 29
- * **htest**
 - np.boot, 8
 - np.cor.test, 13
 - np.loc.test, 16
 - np.reg.test, 22
 - plot, 29
- * **models**
 - np.reg.test, 22
- * **multivariate**
 - np.boot, 8
 - np.loc.test, 16
 - np.reg.test, 22
- * **nonparametric**
 - np.boot, 8
 - np.cor.test, 13
 - np.loc.test, 16
 - np.reg.test, 22
 - plot, 29
- * **package**
 - nptest-package, 2
- * **regression**
 - np.reg.test, 22
- * **robust**
 - np.cor.test, 13
 - np.loc.test, 16
 - np.reg.test, 22
- * **univar**
 - np.boot, 8
 - np.cor.test, 13
 - np.loc.test, 16
 - np.reg.test, 22
- * **utilities**
 - flipn, 5
 - mcse, 6
 - permn, 27