

Package ‘rsf’

October 14, 2022

Type Package

Title Report of Statistical Findings in 'bookdown'

Version 0.3.0

Description A report of statistical findings (RSF) project template is generated using a 'bookdown' format. 'YAML' fields can be further customized. Additional helper functions provide extra features to the RSF.

License MIT + file LICENSE

URL <https://github.com/dchiu911/rsf/>, <https://dchiu911.github.io/rsf/>

BugReports <https://github.com/dchiu911/rsf/issues>

Imports bookdown, gert, here, knitr, magrittr, renv, rlang, usethis, yaml, ymlthis

Encoding UTF-8

RoxygenNote 7.2.1

NeedsCompilation no

Author Derek Chiu [aut, cre]

Maintainer Derek Chiu <dchiu@bccrc.ca>

Repository CRAN

Date/Publication 2022-09-15 19:26:09 UTC

R topics documented:

git_ignore_outputs	2
use_references	2
use_rsf	3

Index

4

<code>git_ignore_outputs</code>	<i>Git ignore generated outputs</i>
---------------------------------	-------------------------------------

Description

Add generated reports, figures, and HTML libraries to `.gitignore`

Usage

```
git_ignore_outputs(path = ".", figs_only = TRUE)
```

Arguments

<code>path</code>	path of the directory containing the input files <code>.gitignore</code> and <code>_bookdown.yml</code> .
<code>figs_only</code>	logical; if TRUE (default), only figures are git ignored.

Examples

```
wd <- tempdir()
savedir <- setwd(wd)
file.copy(list.files(system.file("extdata", package = "rsf"),
                     full.names = TRUE, all.files = TRUE, no.. = TRUE), ".")
file.rename("gitignore", ".gitignore")
git_ignore_outputs(figs_only = FALSE)
setwd(savedir)
```

<code>use_references</code>	<i>Use references</i>
-----------------------------	-----------------------

Description

Add a References section at the end of the RSF.

Usage

```
use_references(path = ".", number = 99)
```

Arguments

<code>path</code>	path of the directory containing the input files <code>index.Rmd</code> , <code>_output.yml</code> , <code>preamble.tex</code> .
<code>number</code>	number prepended to references Rmd source file.

Examples

```
wd <- tempdir()
savedir <- setwd(wd)
file.copy(list.files(system.file("extdata", package = "rsf"),
                     full.names = TRUE), ".")
use_references(number = 4)
setwd(savedir)
```

use_rsf

Use RSF project template

Description

Opens a new R project using the RSF template. Intended for use in RStudio, not interactively.

Usage

```
use_rsf(path, ...)
```

Arguments

path	project path
...	project configurations supported:
	<ul style="list-style-type: none">• <code>output_dir</code> in <code>_bookdown.yml</code> https://bookdown.org/yihui/bookdown/configuration.html• initialize git repo via <code>gert::git_init()</code>• initialize renv via <code>renv::init()</code>

Details

This function is called when the user selects File > New Project > New Directory > Report of Statistical Findings using bookdown. The directory name and output directory can be specified.

Index

gert::git_init(), [3](#)
git_ignore_outputs, [2](#)
renv::init(), [3](#)
use_references, [2](#)
use_rsf, [3](#)