

Package ‘vcpen’

October 12, 2022

Type Package

Title Penalized Variance Components Analysis

Version 1.9

Date 2022-01-02

Description Method to perform penalized variance component analysis.

License GPL (>= 3)

Suggests rmarkdown, testthat

Depends R (>= 4.0.0), methods

Imports knitr, Rcpp (>= 1.0.0), RcppArmadillo (>= 0.8.0)

LinkingTo Rcpp, RcppArmadillo

NeedsCompilation yes

RoxygenNote 7.1.2

VignetteBuilder knitr

URL <https://cran.r-project.org/package=vcpen>

Author Jason Sinnwell [aut, cre] (<<https://orcid.org/0000-0003-1964-5522>>),
Daniel Schaid [aut] (<<https://orcid.org/0000-0003-1457-6433>>)

Maintainer Jason Sinnwell <sinnwell.jason@mayo.edu>

Repository CRAN

Date/Publication 2022-01-03 16:40:02 UTC

R topics documented:

kernel_linear	2
minque	2
vcexample	3
vcpen	4

Index

7

kernel_linear *Variance Component Linear Kernel Matrix*

Description

Variance component Linear kernel matrix from genotype dosage

Usage

```
kernel_linear(dose, method = "linear")
```

Arguments

dose	data.frame or matrix with
method	type of kernel; currently only linear kernel implemented

Value

square symmetric kernel matrix for subject similarity by genotype dosage

Author(s)

JP Sinnwell, DJ Schaid

See Also

[vcpen](#)

Examples

```
data(vcexample)
Kern1 <- kernel_linear(dose[,which(doseinfo[,1]==1)], method="linear")
Kern1[1:5,1:5]
```

minque *MINQUE estimation of variance components*

Description

Estimate variance components by MINQUE method, allowing multiple iterations

Usage

```
minque(y, X, Kerns, n.iter = 1, eps = 0.001)
```

Arguments

y	Numeric vector of traits. Only continuous trait currently allowed.
X	Matrix of covariates (columns) for subjects (rows), matching subjects in the trait (y) vector.
Kerns	List of kernel matrices: a kernel matrix for each variance component. The last kernel matrix in the list (an identity matrix) is for the residual variance component.
n.iter	Number of minque iterations
eps	Default small positive value for non-positive vc estimates within iterations.

Value

List with estimates of variance components (vc), covariate regression coefficients (beta), and residuals of model fit.

Author(s)

JP Sinnwell, DJ Schaid

Examples

```
data(vcexample)
nvc <- 1+length(unique(doseinfo[,2]))
id <- 1:nrow(dose)
## vcs for genetic kernel matrices
Kerns <- vector("list", length=nvc)
for(i in 1:(nvc-1)){
  Kerns[[i]] <- kernel_linear(dose[,grep(i, doseinfo[,2])])
  rownames(Kerns[[i]]) <- id
  colnames(Kerns[[i]]) <- id
}
## vc for residual variance
Kerns[[nvc]] <- diag(nrow(dose))
rownames(Kerns[[nvc]]) <- id
colnames(Kerns[[nvc]]) <- id
prefit <- minque(response, covmat, Kerns, n.iter=2)
prefit[1]
prefit[2]
fit <- vcpen(response, covmat, Kerns, vc_init = prefit$vc)
```

Description

Datasets for an example run of vcpen with 4 variance components calculated as kernel matrices from genotype dosage (dose) on 100 subjects with two covariates (covmat), and a continuous response.

Format

The example contains three data.frames and a response vector for 100 subjects at 70 SNPs accross 4 variance components:

```
covmat two arbitrary covariates (columns) for 100 subjects (rows)
dose genotype dosage at 70 SNPs (columns) and 100 subjects (rows)
doseinfo 2-column matrix with indices for grouping SNPs into variance components (for Kernel
Matrix)
response continuous response vector for 100 subjects
```

Examples

```
data(vcexample)
dim(dose)
dim(doseinfo)
dim(covmat)
length(response)
```

vcpen

Penalized Variance Components

Description

Penalized Variance Component analysis

Usage

```
vcpen(
  y,
  X,
  Kerns,
  frac1 = 0.8,
  lambda_factor = NULL,
  lambda_grid = NULL,
  maxiter = 1000,
  vc_init = NULL,
  print_iter = FALSE
)

## S3 method for class 'vcpen'
summary(object, ..., digits = 4)
```

Arguments

y	Numeric vector of traits. Only continuous trait currently allowed.
X	Matrix of covariates (columns) for subjects (rows), matching subjects in the trait (y) vector.
Kerns	List of kernel matrices: a kernel matrix for each variance component. The last kernel matrix in the list (an identity matrix) is for the residual variance component.
frac1	Fraction of penalty imposed on L1 penalty, between 0 and 1 (0 for only L2; 1 for only L1 penalty).
lambda_factor	Weight for each vc (values between 0 and 1) for how much it should be penalized: 0 means no penalty. Default value of NULL implies weight of 1 for all vc's.
lambda_grid	Vector of lambda penalties for fitting the penalized model. Best to order values from largest to smallest so parameter estimates from a large penalty can be used as initial values for the next smaller penalty. Default value of NULL implies initial values of seq(from=.10, to=0, by=-0.01).
maxiter	Maximum number of iterations allowed during penalized fitting.
vc_init	Numeric vector of initial values for variance components. Default value of NULL implies initial values determined by 2 iterations of minque estimation.
print_iter	Logical: if TRUE, print the iteration results (mainly for refined checks)
object	Fitted vcpen object (used in summary method)
...	Optional arguments for summary method
digits	Significant digits for summary method

Value

object with S3 class vcpen

Author(s)

JP Sinnwell, DJ Schaid

Examples

```
data(vcexample)
nvc <- 1+length(unique(doseinfo[,2]))
id <- 1:nrow(dose)
## vcs for genetic kernel matrices
Kerns <- vector("list", length=nvc)
for(i in 1:(nvc-1)){
  Kerns[[i]] <- kernel_linear(dose[,grep(i, doseinfo[,2])])
  rownames(Kerns[[i]]) <- id
  colnames(Kerns[[i]]) <- id
}
## vc for residual variance
Kerns[[nvc]] <- diag(nrow(dose))
```

```
rownames(Kerns[[nvc]]) <- id  
colnames(Kerns[[nvc]]) <- id  
fit <- vcpen(response, covmat, Kerns, frac1 = .6)  
summary(fit)
```

Index

`covmat (vcexample), 3`
`dose (vcexample), 3`
`doseinfo (vcexample), 3`
`kernel_linear, 2`
`minque, 2`
`response (vcexample), 3`
`summary.vcpn (vcpn), 4`
`vcexample, 3`
`vcpn, 2, 4`