

Package ‘CoImp’

October 17, 2025

Title Parametric and Nonparametric Copula-Based Imputation Methods

Date 2025-10-27

Version 2.1.1

Author Francesca Marta Lilja Di Lascio [aut, cre],
Aurora Gatto [aut],
Simone Giannerini [aut]

Depends R (>= 4.2.0), methods, stats, copula, cluster

Imports nnet, gtools, locfit

Description Copula-based imputation methods: parametric and nonparametric algorithms for missing multivariate data through conditional copulas.

Maintainer Francesca Marta Lilja Di Lascio <marta.dilascio@unibz.it>

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2025-10-17 20:30:08 UTC

Contents

CoImp	2
CoImp-class	5
MAR	7
MAR-class	8
MCAR	9
MCAR-class	11
NPCoImp	12
NPCoImp-class	15
PerfMeasure	16
PerfMeasure-class	18
Index	20

Description

Imputation method based on conditional copula functions.

Usage

```
CoImp(X, n.marg = ncol(X), x.up = NULL, x.lo = NULL, q.up = rep(0.85, n.marg),
      q.lo = rep(0.15, n.marg), type.data = "continuous", smoothing =
      rep(0.5, n.marg), plot = TRUE, model = list(normalCopula(0.5,
      dim=n.marg), claytonCopula(10, dim=n.marg), gumbelCopula(10,
      dim=n.marg), frankCopula(10, dim=n.marg), tCopula(0.5,
      dim=n.marg,...), rotCopula(claytonCopula(10,dim=n.marg),
      flip=rep(TRUE,n.marg)),...), start. = NULL, ...)
```

Arguments

<code>X</code>	a data matrix with missing values. Missing values should be denoted with NA.
<code>n.marg</code>	the number of variables in X.
<code>x.up</code>	a numeric vector of length <code>n.marg</code> with the upper value of each margin used in the Hit or Miss method. Specify either <code>x.up</code> xor <code>q.up</code> .
<code>x.lo</code>	a numeric vector of length <code>n.marg</code> with the lower value of each margin used in the Hit or Miss method. Specify either <code>x.lo</code> xor <code>q.lo</code> .
<code>q.up</code>	a numeric vector of length <code>n.marg</code> with the probability of the quantile used to define <code>x.up</code> for each margin. Specify either <code>x.up</code> xor <code>q.up</code> .
<code>q.lo</code>	a numeric vector of length <code>n.marg</code> with the probability of the quantile used to define <code>x.lo</code> for each margin. Specify either <code>x.lo</code> xor <code>q.lo</code> .
<code>type.data</code>	the nature of the variables in X: discrete or continuous.
<code>smoothing</code>	values for the nearest neighbour component of the smoothing parameter of the lp function.
<code>plot</code>	logical: if TRUE plots the estimated marginal densities and a bar plot of the percentages of missing and available data for each margin.
<code>model</code>	a list of copula models to be used for the imputation, see the Details section. This should be one of normal and t (with <code>dispstr</code> as in the copula package), frank, clayton, gumbel, and rotated copulas. As in fitCopula , itau fitting coerced tCopula to 'df.fixed=TRUE'.
<code>start.</code>	a numeric vector of starting values for the parameter optimization via optim .
<code>...</code>	further parameters for fitCopula , lp and further graphical arguments.

Details

CoImp is an imputation method based on conditional copula functions that allows to impute missing observations according to the multivariate dependence structure of the generating process without any assumptions on the margins. This method can be used independently from the dimension and the kind (monotone or non monotone) of the missing patterns.

Brief description of the approach:

1. estimate both the margins and the copula model on available data by means of the semi-parametric sequential two-step inference for margins;
2. derive conditional density functions of the missing variables given non-missing ones through the corresponding conditional copulas obtained by using the Bayes' rule;
3. impute missing values by drawing observations from the conditional density functions derived at the previous step. The Monte Carlo method used is the Hit or Miss.

The estimation approach for the copula fit is semiparametric: a range of nonparametric margins and parametric copula models can be selected by the user.

Value

An object of S4 class "CoImp", which is a list with the following elements:

<code>Missing.data.matrix</code>	the original missing data matrix to be imputed.
<code>Perc.miss</code>	the matrix of the percentage of missing and available data.
<code>Estimated.Model</code>	the estimated copula model on the available data.
<code>Estimation.Method</code>	the estimation method used for the copula <code>Estimated.Model</code> .
<code>Index.matrix.NA</code>	matrix indices of the missing data.
<code>Smooth.param</code>	the smoothing parameter alpha selected on the basis of the AIC.
<code>Imputed.data.matrix</code>	the imputed data matrix.
<code>Estimated.Model.Imp</code>	the estimated copula model on the imputed data matrix.
<code>Estimation.Method.Imp</code>	the estimation method used for the copula <code>Estimated.Model.Imp</code> .

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>, Simone Giannerini <simone.giannerini@unibo.it>

References

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.

Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[NPCoImp](#), [MCAR](#), [MAR](#), [fitCopula](#), [lp](#).

Examples

```
## generate data from a 4-variate Frank copula with different margins

set.seed(21)
n.marg <- 4
theta <- 5
copula <- frankCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("norm", "gamma", "beta", "gamma"), list(list(mean=7, sd=2),
list(shape=3, rate=2), list(shape1=4, shape2=1), list(shape=4, rate=3)))
n <- 20
x.samp <- copula::rMvdc(n, mymvdc)

# randomly introduce univariate and multivariate missing

perc.mis <- 0.3
set.seed(11)
miss.row <- sample(1:n, perc.mis*n, replace=TRUE)
miss.col <- sample(1:n.marg, perc.mis*n, replace=TRUE)
miss <- cbind(miss.row, miss.col)
x.samp.miss <- replace(x.samp, miss, NA)

# impute missing values

imp <- CoImp(x.samp.miss, n.marg=n.marg, smoothing = rep(0.6, n.marg), plot=TRUE,
  type.data="continuous", model=list(normalCopula(0.5, dim=n.marg),
  frankCopula(10, dim=n.marg), gumbelCopula(10, dim=n.marg)));

# methods show and plot

show(imp)
plot(imp)
```

```
## Not run:
## generate data from a 3-variate Clayton copula and introduce missing by
## using the MCAR function and try to impute through a rotated copula

set.seed(11)
n.marg <- 3
theta <- 5
copula <- claytonCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("beta", "beta", "beta"), list(list(shape1=4, shape2=1),
  list(shape1=.5, shape2=.5), list(shape1=2, shape2=3)))
n <- 50
x.samp <- copula::rMvdc(n, mymvdc)

# randomly introduce MCAR univariate and multivariate missing

perc.miss <- 0.15
setseed <- set.seed(13)
x.samp.miss <- MCAR(x.samp, perc.miss, setseed)
x.samp.miss <- x.samp.miss@"db.missing"

# impute missing values

imp <- CoImp(x.samp.miss, n.marg=n.marg, smoothing = c(0.45,0.2,0.5), plot=TRUE,
  q.lo=rep(0.1,n.marg), q.up=rep(0.9,n.marg), model=list(claytonCopula(0.5,
  dim=n.marg), rotCopula(claytonCopula(0.5,dim=n.marg))));

# methods show and plot

show(imp)
plot(imp)

## End(Not run)
```

CoImp-class

Class "CoImp"

Description

A class for CoImp and its extensions

Objects from the Class

Objects can be created by calls of the form `new("CoImp", ...)`.

Slots

Missing.data.matrix: Object of class "matrix". Original missing data matrix to be imputed.

Perc.miss: Object of class "matrix". Missing and available data percentage for each variable.

Estimated.Model: Object of class "list". The list contains:

model	the copula model selected and estimated on the complete cases.
dimension	the dimension of the model.
parameter	the estimated dependence parameter of the model.
number	the index of the estimated model in the list of models given in input.

Estimation.Method: Object of class "character". The estimation method used for the copula model in **Estimated.Model**. Allowed methods are in [fitCopula](#).

Index.matrix.NA: Object of class "matrix". Matrix of row and column indexes of missing data.

Smooth.param: Object of class "numeric". The values of the nearest neighbor component of the smoothing parameter of the lp function.

Imputed.data.matrix Object of class "matrix". The imputed data matrix.

Estimated.Model.Imp Object of class "list". The list contains:

model	the copula model selected and estimated on the imputed cases.
dimension	the dimension of the model.
parameter	the estimated dependence parameter of the model.
number	the index of the estimated model in the list of models given in input.

Estimation.Method.Imp Object of class "character". The estimation method used for the copula model in **Estimated.Model.Imp**. Allowed methods are in [fitCopula](#).

Methods

plot signature(x = "CoImp", y = "missing"): ...

show signature(object = "CoImp"): ...

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>, Simone Giannerini <simone.giannerini@unibo.it>

References

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.

Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[NPCoImp](#), [MCAR](#), [MAR](#), [fitCopula](#).

Examples

```
showClass("CoImp")
```

MAR

Generation of multivariate missing at random (MAR) data

Description

Introduction of artificial missing at random (MAR) data in a given data set. Missing values are multivariate and have generic pattern.

Usage

```
MAR(db.complete, perc.miss = 0.3, setseed = 13, mcols = NULL, ...)
```

Arguments

<code>db.complete</code>	the complete data matrix.
<code>perc.miss</code>	the percentage of missing values to be generated.
<code>setseed</code>	the seed for the generation of the missing values.
<code>mcols</code>	the index of the columns in which to introduce MAR values.
<code>...</code>	further parameters for fitCopula .

Details

MAR introduce artificial missing at random values in a given complete data set. Missing values are univariate and multivariate and have generic pattern.

Value

An object of S4 class "MAR", which is a list with the following element:

<code>perc.record.missing</code>	Object of class "numeric". A percentage value.
<code>db.missing</code>	Object of class "matrix". A data set with artificial multivariate MAR.

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>,
 Simone Giannerini <simone.giannerini@unibo.it>

References

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.

Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[CoImp](#), [NPCoImp](#), [fitCopula](#).

Examples

```
# generate data from a 4-variate Gumbel copula with different margins

set.seed(11)
n.marg <- 4
theta <- 5
copula <- frankCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("norm", "gamma", "beta", "gamma"), list(list(mean=7, sd=2),
list(shape=3, rate=2), list(shape1=4, shape2=1), list(shape=4, rate=3)))
n <- 30
x.samp <- rMvdc(n, mymvdc)

# apply MAR by introducing 30% of missing data

mar <- MAR(db.complete = x.samp, perc.miss = 0.3, setseed = 11)

mar
```

MAR-class

Class "MAR"

Description

A class for MAR and its extensions

Objects from the Class

Objects can be created by calls of the form `new("MAR", ...)`.

Slots

`perc.record.missing`: Object of class "numeric". A percentage value.

`db.missing`: Object of class "matrix". A data set with artificial multivariate MAR with generic pattern.

Methods

`show signature(object = "MAR")`: ...

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>, Simone Giannerini <simone.giannerini@unibo.it>

References

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.

Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[CoImp](#), [NPCoImp](#).

Examples

```
showClass("MAR")
```

MCAR

Generation of multivariate MCAR data

Description

Introduction of artificial missing completely at random (MCAR) data in a given data set. Missing values are multivariate and have generic pattern.

Usage

```
MCAR(db.complete, perc.miss = 0.3, setseed = 13, mcols = NULL, ...)
```

Arguments

<code>db.complete</code>	the complete data matrix.
<code>perc.miss</code>	the percentage of missing value to be generated.
<code>setseed</code>	the seed for the generation of the missing values.
<code>mcols</code>	the index of the columns in which to introduce MCAR values.
<code>...</code>	further parameters for fitCopula .

Details

MCAR introduce artificial missing completely at random values in a given complete data set. Missing values are multivariate and have generic pattern.

Value

An object of S4 class "MCAR", which is a list with the following element:

`db.missing` Object of class "matrix". A data set with artificial multivariate MCAR.

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>,
Simone Giannerini <simone.giannerini@unibo.it>

References

- Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.
- Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.
- Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[CoImp](#), [NPCoImp](#), [fitCopula](#).

Examples

```
# generate data from a 4-variate Gumbel copula with different margins

set.seed(11)
n.marg <- 4
theta <- 5
```

```

copula <- frankCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("norm", "gamma", "beta", "gamma"), list(list(mean=7, sd=2),
list(shape=3, rate=2), list(shape1=4, shape2=1), list(shape=4, rate=3)))
n      <- 30
x.samp <- rMvdc(n, mymvdc)

# apply MCAR by introducing 30% of missing data

mcar   <- MCAR(db.complete = x.samp, perc.miss = 0.3, setseed = 11)

mcar

# same example as above but introducing missing only in the first and third column

mcar2  <- MCAR(db.complete = x.samp, perc.miss = 0.3, setseed = 11, mcols=c(1,3))

mcar2

```

MCAR-class

Class "MCAR"

Description

A class for MCAR and its extensions

Objects from the Class

Objects can be created by calls of the form `new("MCAR", ...)`.

Slots

`db.missing`: Object of class "matrix". A data set with artificial multivariate MCAR.

Methods

`show` signature(object = "MCAR"): ...

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>,
 Simone Giannerini <simone.giannerini@unibo.it>

References

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.

Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[CoImp](#), [NPCoImp](#).

Examples

```
showClass("MCAR")
```

NPCoImp

Nonparametric Copula-Based Imputation Method

Description

Imputation method based on empirical copula-based conditional cumulative probability functions.

Usage

```
NPCoImp(X, Psi=seq(0.05,0.45,by=0.05), smoothing="beta", K=7, method="gower", ...)
```

Arguments

X	a data matrix with missing values. Missing values should be denoted with NA.
Psi	vector of probabilities to evaluate the radial symmetry/asymmetry of the empirical copula-based conditional cumulative probability function and find the best lower-orthant quantile for the imputation (see below for details).
smoothing	the character string specifying the type of smoothing of the empirical copula. Default is "beta" (empirical beta copula) but also "none" (the original empirical copula) can be used.
K	the number of data matrix rows more similar to the missing one that are used for the imputation.
method	the distance measure used for the imputation, among Euclidean, Manhattan, Canberra, Gower, and two based on the Kendall-correlation coefficient (see below for details).
...	further parameters for daisy, e.g. weights.

Details

NPCoImp is a nonparametric imputation method based on the empirical copula-based conditional cumulative probability functions. To choose the best lower-orthant quantile for the imputation it evaluates the radial (a)symmetry of the empirical copula-based conditional cumulative probability functions and it uses the K pseudo-observations more similar to the missing one. The NPCoImp allows the imputation of missing observations according to the multivariate dependence structure of the data generating process without any assumptions on the margins. This method can be used independently from the dimension and the kind (monotone or non monotone) of the missing patterns. Brief description of the approach:

1. estimate the empirical copula-based conditional cumulative probability function of the missing observation(s) given the available ones;
2. evaluate the radial (a)symmetry of the empirical copula-based cumulative probability distribution function around 0.5 (see the paper in the references for details);
3. select the lower-orthant quantile of the empirical copula-based conditional cumulative probability function on the basis of its radial (a)symmetry (see the paper in the references for details);
4. select the K pseudo-observations closest to the imputed one and the corresponding original observations;
5. impute missing values by replacing them from the average of the original observations derived at the previous step;
6. calculate the empirical copula-based conditional cumulative probability function of the lower-orthant quantile used for imputing.

Value

An object of S4 class "NPCoImp", which is a list with the following elements:

<code>Imputed.matrix</code>	the imputed data matrix.
<code>Selected.alpha</code>	the (conditional) probability of the lower-orthant quantile selected for the imputation.
<code>numFlat</code>	the number of possible flat empirical copula-based conditional cumulative probability functions, i.e. when the copula is always zero.

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>, Aurora Gatto <aurora.gatto@unibz.it>

References

Di Lascio, F.M.L., Gatto A. (202x) "A nonparametric copula-based imputation method". Under review.

See Also

[CoImp](#), [MCAR](#), [MAR](#).

Examples

```
## generate data from a 4-variate Frank copula with different margins

set.seed(21)
n.marg <- 4
theta <- 5
copula <- frankCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("norm", "gamma", "beta", "gamma"), list(list(mean=7, sd=2),
list(shape=3, rate=2), list(shape1=4, shape2=1), list(shape=4, rate=3)))
n <- 20
x.samp <- copula::rMvdc(n, mymvdc)

# randomly introduce univariate and multivariate missing

perc.mis <- 0.25
set.seed(14)
miss.row <- sample(1:n, perc.mis*n, replace=TRUE)
miss.col <- sample(1:n.marg, perc.mis*n, replace=TRUE)
miss <- cbind(miss.row, miss.col)
x.samp.miss <- replace(x.samp, miss, NA)
x.samp.miss
probs <- seq(0.05, 0.45, by=0.1)
ndist <- 7
dist.meth <- "gower"

# impute missing values
NPimp <- NPCoImp(X=x.samp.miss, Psi=probs, smoothing="beta", K=ndist,
method=dist.meth)

# methods show

show(NPimp)

## Not run:
## generate data from a 3-variate Clayton copula and introduce missing by
## using the MCAR function and try to impute through a rotated copula

set.seed(11)
n.marg <- 3
theta <- 5
copula <- claytonCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("beta", "beta", "beta"), list(list(shape1=4, shape2=1),
list(shape1=.5, shape2=.5), list(shape1=2, shape2=3)))
n <- 50
x.samp <- copula::rMvdc(n, mymvdc)

# randomly introduce MCAR univariate and multivariate missing

perc.miss <- 0.15
setseed <- set.seed(13)
x.samp.miss <- MCAR(x.samp, perc.miss, setseed)
x.samp.miss <- x.samp.miss@"db.missing"
```

```

probs <- seq(0.05,0.45,by=0.05)
ndist <- 7
dist.meth <- "gower"

# impute missing values

NPimp2 <- NPCoImp(X=x.samp.miss, Psi=probs, smoothing="beta", K=ndist,
                 method=dist.meth)

# methods show and plot

show(NPimp2)

## End(Not run)

```

NPCoImp-class

Class "NPCoImp"

Description

A class for NPCoImp and its extensions

Objects from the Class

Objects can be created by calls of the form `new("NPCoImp", ...)`.

Slots

`Imputed.matrix` Object of class "matrix". The imputed data matrix.

`Selected.alpha` Object of class "vector". The (conditional) probability of the lower-orthant quantile selected for the imputation.

`numFlat` Object of class "numeric". The number of possible flat empirical copula-based conditional probability functions, i.e. when the function cannot be empirically estimated.

Methods

`show` `signature(object = "NPCoImp")`: ...

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>, Aurora Gatto <aurora.gatto@unibz.it>

References

Di Lascio, F.M.L, Gatto A. (202x) "A nonparametric copula-based imputation method". Under review.

See Also

[CoImp](#), [MCAR](#), [MAR](#).

Examples

```
showClass("NPCoImp")
```

PerfMeasure	<i>Performance measures for evaluating the goodness of an imputed database</i>
-------------	--

Description

Set of measures useful to evaluate the goodness of the used imputation method.

Usage

```
PerfMeasure(db.complete, db.imputed, db.missing, n.marg = 2, model =  
            list(normalCopula(0.5, dim=n.marg), claytonCopula(10,  
                    dim=n.marg), gumbelCopula(10, dim=n.marg), frankCopula(10,  
                    dim=n.marg), tCopula(0.5, dim=n.marg,...),  
            rotCopula(claytonCopula(10,dim=n.marg),flip=rep(TRUE,n.marg)),  
            ...), ...)
```

Arguments

db.complete	the complete data matrix.
db.imputed	the imputed data matrix.
db.missing	the data matrix with NA data.
n.marg	the number of variables in db.complete.
model	a list of copula models to be used for the imputation. See the Details section. This should be one of normal and t (with dispstr as in the copula package), frank, clayton, gumbel, and rotated copulas. As in fitCopula, itau fitting coerced tCopula to 'df.fixed=TRUE'.
...	further parameters for fitCopula .

Details

PerfMeasure computes some measures useful for evaluating the goodness of the used imputation method. PerfMeasure requires in input the imputed, the complete and the missing data matrix and gives in output five different measures of performance. See below for details

Value

An object of S4 class "PerfMeasure", which is a list with the following elements:

MARE	Object of class "numeric". The mean (on the replications performed) of the absolute relative error between the imputed and the corresponding original value.
RB	Object of class "numeric". The relative bias of the estimator for the dependence parameter.
RRMSE	Object of class "numeric". The relative root mean squared error of the estimator for the dependence parameter.
TID	Object of class "vector". Upper and lower tail dependence indexes for bivariate copulas. Original function is in tailIndex .

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>,
 Simone Giannerini <simone.giannerini@unibo.it>

References

- Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.
- Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.
- Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[CoImp](#), [NPCoImp](#), [MCAR](#), [MAR](#).

Examples

```
## Not run:
# generate data from a 4-variate Gumbel copula with different margins

set.seed(11)
n.marg <- 4
theta <- 5
copula <- frankCopula(theta, dim = n.marg)
mymvdc <- mvdc(copula, c("norm", "gamma", "beta", "gamma"), list(list(mean=7, sd=2),
  list(shape=3, rate=2), list(shape1=4, shape2=1), list(shape=4, rate=3)))
n <- 20
x.samp <- rMvdc(n, mymvdc)
```

```

# randomly introduce univariate and multivariate missing

perc.mis    <- 0.3
set.seed(11)
miss.row    <- sample(1:n, perc.mis*n, replace=TRUE)
miss.col    <- sample(1:n.marg, perc.mis*n, replace=TRUE)
miss        <- cbind(miss.row,miss.col)
x.samp.miss <- replace(x.samp,miss,NA)

# impute missing values

imp <- CoImp(x.samp.miss, n.marg=n.marg, smoothing=rep(0.6,n.marg), plot=TRUE,
            type.data="continuous");
imp

# apply PerfMeasure to the imputed data set

pm <- PerfMeasure(db.complete=x.samp, db.missing=x.samp.miss,
                 db.imputed=imp@"Imputed.data.matrix", n.marg=4)

pm
str(pm)

## End(Not run)

```

PerfMeasure-class	<i>Class "PerfMeasure"</i>
-------------------	----------------------------

Description

A class for PerfMeasure and its extensions

Objects from the Class

Objects can be created by calls of the form `new("PerfMeasure", ...)`.

Slots

MARE: Object of class "numeric". The mean (on the replications performed) of the absolute relative error between the imputed and the corresponding original value.

RB: Object of class "numeric". The relative bias of the estimator for the dependence parameter.

RRMSE: Object of class "numeric". The relative root mean squared error of the estimator for the dependence parameter.

TID: Object of class "vector". Upper and lower tail dependence indexes for bivariate copulas. Original function is in [tailIndex](#).

Methods

```
show signature(object = "PerfMeasure"): ...
```

Author(s)

F. Marta L. Di Lascio <marta.dilascio@unibz.it>, Simone Giannerini <simone.giannerini@unibo.it>

References

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2015) "Exploring Copulas for the Imputation of Complex Dependent Data". *Statistical Methods & Applications*, 24(1), p. 159-175. DOI 10.1007/s10260-014-0287-2.

Di Lascio, F.M.L., Giannerini, S. and Reale, A. (2014) "Imputation of complex dependent data by conditional copulas: analytic versus semiparametric approach", *Book of proceedings of the 21st International Conference on Computational Statistics (COMPSTAT 2014)*, p. 491-497. ISBN 9782839913478.

Bianchi, G. Di Lascio, F.M.L. Giannerini, S. Manzari, A. Reale, A. and Ruocco, G. (2009) "Exploring copulas for the imputation of missing nonlinearly dependent data". *Proceedings of the VII Meeting Classification and Data Analysis Group of the Italian Statistical Society (Cladag)*, Editors: Salvatore Ingrassia and Roberto Rocci, Cleup, p. 429-432. ISBN: 978-88-6129-406-6.

See Also

[CoImp](#), [NPCoImp](#), [MCAR](#), [MAR](#).

Examples

```
showClass("PerfMeasure")
```

Index

* **classes**

CoImp-class, [5](#)
MAR-class, [8](#)
MCAR-class, [11](#)
NPCoImp-class, [15](#)
PerfMeasure-class, [18](#)

* **copula**

CoImp, [2](#)
MAR, [7](#)
MCAR, [9](#)
PerfMeasure, [16](#)

* **imputation**

CoImp, [2](#)
MAR, [7](#)
MCAR, [9](#)
PerfMeasure, [16](#)

* **multivariate**

CoImp, [2](#)
MAR, [7](#)
MCAR, [9](#)
PerfMeasure, [16](#)

CoImp, [2](#), [8–10](#), [12](#), [13](#), [16](#), [17](#), [19](#)

CoImp-class, [5](#)

fitCopula, [2](#), [4](#), [6–8](#), [10](#), [16](#)

lp, [2](#), [4](#)

MAR, [4](#), [7](#), [7](#), [13](#), [16](#), [17](#), [19](#)

MAR-class, [8](#)

MCAR, [4](#), [7](#), [9](#), [13](#), [16](#), [17](#), [19](#)

MCAR-class, [11](#)

NPCoImp, [4](#), [7–10](#), [12](#), [12](#), [17](#), [19](#)

NPCoImp-class, [15](#)

optim, [2](#)

PerfMeasure, [16](#)

PerfMeasure-class, [18](#)

plot, CoImp, missing-method
(CoImp-class), [5](#)

show, CoImp-method (CoImp-class), [5](#)

show, NPCoImp-method (NPCoImp-class), [15](#)

show, PerfMeasure-method
(PerfMeasure-class), [18](#)

tailIndex, [17](#), [18](#)