

Package ‘emplikAUC’

November 6, 2025

Version 0.5

Title Empirical Likelihood Ratio Test/Confidence Interval for AUC or pAUC

Maintainer Mai Zhou <maizhou@gmail.com>

Depends R (>= 3.2.5), emplik2, rootSolve

Imports stats

Description Test hypotheses and construct confidence intervals for AUC (area under Receiver Operating Characteristic curve) and pAUC (partial area under ROC curve), from the given two samples of test data with disease/healthy subjects. The method used is based on TWO SAMPLE empirical likelihood and PROFILE empirical likelihood, as described in
<<https://www.ms.uky.edu/~mai/research/eAUC1.pdf>>.

License GPL (>= 2)

NeedsCompilation no

Author Mai Zhou [aut, cre, cph],
Xue Ding [aut],
Yumin Zhao [aut]

Repository CRAN

Date/Publication 2025-11-06 07:10:03 UTC

Contents

EL2paucT1T2	2
el2test4auc	3
el2testPauc	5
el2testPaucT	6
eltest4aucONE	7
eltest4diff2auc	9
eltest4paucONE	10
eltest4paucT	11
findLnew	13
findULNEW	14

findUnew	15
myEstPaucT	17
New.el2.test	18
quantONE	19
smooth0	20
smooth3	21
smooth3vec	22
smooth5vec	23
smoothLvec	24

Index	26
--------------	-----------

EL2paucT1T2	<i>Testing one pAUC(p1, p2) and two quantile values together by Empirical Likelihood.</i>
-------------	---

Description

This function computes the two sample Log Empirical Likelihood ratio for testing H_0 : $pAUC(p1, p2) = \theta$; $F(\tau_1) = 1 - p_2$; $F(\tau_2) = 1 - p_1$. The two samples are in the x-vector and y-vector.

Usage

```
EL2paucT1T2(tauVec, pauc, partial1, partial2, x, y, epsxy)
```

Arguments

tauVec	The vector (tau1, tau2), the two quantile values, to be tested.
pauc	The value of the pAUC(p1, p2) under H_0 , to be tested.
partial1	The probability that define the quantile 1
partial2	The probability that define the quantile 2. Must satisfy partial 1 < partial 2 .
x	a vector of observations, length m, for the first sample.
y	a vector of observations, length n, for the second sample.
epsxy	The parameter for smoothing when compare x-y.

Details

The input tauVec=(tau1, tau2), and must have: tau1 < tau2. The relevant definitions are: tau1 = $F^{-1}(1 - \text{partial2})$; tau2 = $F^{-1}(1 - \text{partial1})$. Thus, we must have partial2 > partial1.

This function is testing 3 parameters simultaneously. It depends on the package `empLk2`.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad s.t. \quad \sum v_i = 1, \quad \sum \nu_j = 1.$$

Value

A single value that is the "-2LLR" from `emplik2::el2.cen.EMm()`. Typically should be distributed as chi square $df=3$, under H_0 .

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

el2test4auc

Testing one AUC value by Empirical likelihood.

Description

By calling upon a function from the package `emplik2` (using EM), this function computes the two sample Log Empirical Likelihood ratio for testing H_0 : $AUC = \theta$. The two samples are in the x -vector and y -vector inputs.

Usage

```
el2test4auc(theta, x, y, ind)
```

Arguments

<code>theta</code>	The "true" value of the AUC under H_0 , to be tested.
<code>x</code>	a vector of observations, length m , for the first sample. The test-results of healthy subjects.
<code>y</code>	a vector of observations, length n , for the second sample. The test-results of disease subjects.
<code>ind</code>	A smoothed indicator function, to generate a Matrix of (smoothed) indicator values: $I[x[i] < y[j]]$.

Details

This function is similar to the function `eltest4aucONE()`, the difference is that we call the function `emplik2::el2.cen.EMS()` to do the heavy computation (instead of by our own code). So, the speed and convergence property may be slightly different. When they both converge the results should be the same.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1 , \quad \sum \nu_j = 1 .$$

Value

A list that is the same as `el2.cen.EMS()` from `emplik2` package. Which contains

<code>lambda</code>	The final tilting parameter.
<code>"-2LLR"</code>	The -2 log empirical likelihood ratio.
<code>Pval</code>	The p-value.
<code>iterNum</code>	The iteration number used in computing.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
#### The estimation of AUC
sum(smooth3(x=x, y=y))/(length(x)*length(y))
#### This does not work in Rcmd check: (truncate at %%)
#### rep(1/length(x), length(x))**smooth3(x=x, y=y)**rep(1/length(y), length(y))
#### The result should be 0.75.
#### We may then test a hypothesis about the AUC value: H0: AUC= 0.7
el2test4auc(theta=0.7, x=x, y=y, ind=smooth3)
#### Two of the outputs should be '-2LLR'=0.1379561 and Pval=0.7103214
```

el2testPauc

*Testing one pAUC(0, p) value by Empirical likelihood.***Description**

This function computes the two sample Log Empirical Likelihood ratio for testing $H_0: \text{pAUC}(0, p) = \theta$. The two samples are in the x-vector and y-vector inputs.

Usage

```
el2testPauc(theta, x, y, ind, nuilow, nuiup, partial, epsxy, epsT)
```

Arguments

theta	The "true" value of the pAUC(0, p) under H_0 , to be tested.
x	a vector of observations, length m, for the first sample, test-results with the healthy subjects.
y	a vector of observations, length n, for the second sample, test-results with the disease subjects.
ind	The (smoothed) indicator function for compare x-y.
nuilow	Lower bound for the nuisance parameter (1-p)-th quantile of X) search.
nuiup	Upper bound for nuisance parameter search.
partial	The probability p in pAUC(0, p).
epsxy	The smoothing parameter when compare x-y.
epsT	The smoothing parameter when calculating quantile.

Details

This function will call another function: `el2testPaucT()`. We then use `optimize()` to profile out the nuisance parameter tau: the (1-p)-th quantile of X distribution.

Can be used by `findUnew()` etc.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad s.t. \quad \sum v_i = 1, \quad \sum \nu_j = 1.$$

Value

A list containing

"-2LLR"	The -2 log empirical likelihood ratio.
Nupar	The nuisance parameter value that achieved the minimum.
Pval	The p-value, by using chi square distribution with 1 df.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

el2testPaucT	<i>Testing one $pAUC(0, p)$ value and one quantile: $F(\tau) = 1-p$ together by Empirical Likelihood.</i>
--------------	---

Description

This function computes the two sample Log Empirical Likelihood ratio for testing $H_0: pAUC(0, p) = \theta$ and $F(\tau) = 1-p$. (F is the CDF of X). The two samples data are in the x -vector and y -vector inputs. It uses EM.

Usage

```
el2testPaucT(tau, pauc, ind, partial, x, y, epsxy, epsT)
```

Arguments

tau	The "true" value of the $(1-p)$ -th quantile of X -distribution F , to be tested.
pauc	The H_0 value of $pAUC(0, p)$ to be tested.
ind	A smoothed indicator function, to generate a Matrix of (smoothed) indicator values: $I[x[i] < y[j]]$.
partial	The probability p in $pAUC(0, p)$; also the p in $F(\tau) = 1-p$.
x	a vector of observations, length m , for the first sample, test-results with healthy subjects.
y	a vector of observations, length n , for the second sample, test-results with disease subjects.
epsxy	The smoothing parameter when compare x - y .
epsT	The smoothing parameter when compare x to τ , for quantile estimation.

Details

This function is called by `el2testPauc()`. It is listed here stand alone because users may find it useful elsewhere.

It make use of function `smooth3()` and the function `el2.cen.EMm()` from the `emplik2` package.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1, \quad \sum \nu_j = 1.$$

Value

It returns one value that is the "-2LLR". It should have chi square df=2 under H_0 .

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

eltest4aucONE

Testing one AUC value by Empirical likelihood.

Description

This function computes the two sample Log Empirical Likelihood ratio for testing H_0 : AUC = theta. The two samples are in the x-vector and y-vector.

Usage

```
eltest4aucONE(theta, x, y, ind, tol.u, tol.v, tol.H0)
```

Arguments

theta	The "true" value of the AUC under H_0 , to be tested.
x	a vector of observations, length m, for the first sample. The test-results of healthy subjects
y	a vector of observations, length n, for the second sample. The test-results of disease subjects.

ind	A smoothed indicator function, to generate a Matrix of (smoothed) indicator values: $I[x[i] < y[j]]$.
tol.u	Error tol for final u probability vector. Must > 0 .
tol.v	Error tol for final v probability vector. Must > 0 .
tol.H0	The error bound for the constrained NPMLE to satisfy H_0 , must > 0 .

Details

This function is similar to `el2test4auc`, but using our own algorithm (not EM). It may be slightly different to the above in terms of speed and convergence property. We listed 3 kind of tol to control convergence.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1, \quad \sum \nu_j = 1 .$$

Value

A list containing

lambda	The final tilting parameter.
u	the new u vector.
v	The new v vector.
"-2LLR"	The -2 log empirical likelihood ratio.
Pval	The p-value.
iterNum	The iteration number used in computing.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
#### We know the AUC estimator here is 0.75.
#### We may test a hypothesis about the AUC value: H0: AUC= 0.7
eltest4aucONE(theta=0.7, x=x, y=y, ind=smooth3, tol.u=1e-6, tol.v=1e-6, tol.H0=1e-6)
#### Two of the outputs should be '-2LLR'=0.1379561 and Pval=0.7103214
```

eltest4diff2auc	<i>Testing the Difference of 2 AUC values, Paired Data, by Empirical likelihood.</i>
-----------------	--

Description

This function computes the two sample Log Empirical Likelihood ratio for testing H_0 : AUC1-AUC2 = theta. The two samples of paired data are in the x-matrix(mx2) and y-matrix(nx2).

Usage

```
eltest4diff2auc(theta, x, y, ind, tol.u, tol.v, tol.H0)
```

Arguments

theta	The "true" value of the AUC under H_0 , to be tested.
x	a matrix of observations, dim mx2, for the first sample. The test-results of biomarker 1 and 2 on healthy subjects
y	a matrix of observations, dim nx2, for the second sample. The test-results of biomarker 1 and 2 on disease subjects.
ind	A (smoothed) indicator function, to generate a Matrix of (smoothed) indicator values: $I[x[i] < y[j]]$.
tol.u	Error tol for final u probability vector. Must > 0.
tol.v	Error tol for final v probability vector. Must > 0.
tol.H0	The error bound for the constrained NPMLE to satisfy H_0 , must >0.

Details

This function is similar to el2test4auc, but for the difference of 2 AUCs. Using our own algorithm (not EM). We listed 3 kind of tol to control convergence.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1, \quad \sum \nu_j = 1 .$$

Value

A list containing

lambda	The final tilting parameter.
u	the new u vector.
v	The new v vector.
"-2LLR"	The -2 log empirical likelihood ratio.
Pval	The p-value.
Maxiter	The iteration number used in computing.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
#### We know the AUC estimator here is 0.75.
#### We may test a hypothesis about the AUC value: H0: AUC= 0.7
eltest4aucONE(theta=0.7, x=x, y=y, ind=smooth3, tol.u=1e-6, tol.v=1e-6, tol.H0=1e-6)
#### Two of the outputs should be '-2LLR'=0.1379561 and Pval=0.7103214
```

eltest4paucONE	<i>Testing one pAUC value by Empirical likelihood.</i>
----------------	--

Description

This function computes the two sample Log Empirical Likelihood ratio for testing $H_0: \text{pAUC}(0, p) = \theta$. The two samples are in the x-vector and y-vector.

Usage

```
eltest4paucONE(theta, x, y, nuilow, nuiup, ind, partial, epsxy=0.05, epsT=(length(x))^(−0.75))
```

Arguments

theta	The "true" value of the pAUC under H_0 , to be tested.
x	a vector of observations, length m, for the first sample. Test-results with healthy subjects.
y	a vector of observations, length n, for the second sample. Test-results with disease subjects.
nuilow	The lower bound for the nuisance parameter (the (1-p)-th quantile of X CDF F) search.
nuiup	The upper bound for the nuisance parameter search.
ind	A smoothed indicator function, to generate a Matrix of (smoothed) indicator values: $I[x[i] < y[j]]$.
partial	The probability p in the pAUC(0,p).
epsxy	Window width for the smoother, "ind", when compare x-y.
epsT	Window width for the smoother, "ind", when define quantile.

Details

This function calls the function `eltest4paucT`. We then use `optimize()` to profile out the nuisance parameter. Return an empirical likelihood ratio siutable for testing one parameter $\text{pAUC}(0,p)$.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1, \quad \sum \nu_j = 1.$$

Value

A list containing

"-2LLR"	The -2 log empirical likelihood ratio.
Nupar	The nuisance parameter value to achieve the minimum.
Pval	The p-value.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

<code>eltest4paucT</code>	<i>Testing one pAUC and one quantile together by Empirical Likelihood.</i>
---------------------------	--

Description

This function computes the two sample Log Empirical Likelihood ratio for testing $H_0: \text{pAUC}(0,p) = \theta$ and $F(\tau) = 1-p$. The two samples are in the x-vector and y-vector.

Usage

```
eltest4paucT(tau, x, y, true, ind, epsxy, epsT, tol.u, tol.v, tol.H0, p)
```

Arguments

tau	The "true" value of the (1-p)th quantile of X , under H_0 , to be tested.
x	a vector of observations, length m, for the first sample. Test-results with healthy subjects.
y	a vector of observations, length n, for the second sample. Test-results with disease subjects.
true	The H_0 value of the pAUC(0, p) to be tested.
ind	A smoothed indicator function, to generate a Matrix of (smoothed) indicator values: $I[x[i] < y[j]]$.
epsxy	Window width for smoother (ind) when compare x-y.
epsT	Window width for smoother (ind) when find quantile.
tol.u	Error tol for final u probability vector. Must > 0.
tol.v	Error tol for final v probability vector. Must > 0.
tol.H0	The error bound for checking if the constrained NPMLE satisfy H_0 , must > 0.
p	The probability p in pAUC(0, p), and also in $F(\tau) = 1-p$.

Details

This function is similar to `el2testPaucT( )`. Just a different algorithm (not EM). Speed and convergence may be slightly different.

This function is called by `eltest4paucONE`. It is listed here because the user may find it useful elsewhere.

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1, \quad \sum \nu_j = 1.$$

Value

A list containing	
lambda	The final tilting parameter.
u	the new u vector.
v	The new v vector.
"-2LLR"	The -2 log empirical likelihood ratio.
iterNum	The iteration number used in computing.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

findLnew	<i>Finding the Lower bound of a confidence interval for theta by repeatedly testing the hypothesis for the parameter theta.</i>
----------	---

Description

This function try to find the Lower bound of a confidence interval by repeatedly testing the hypothesis for the parameter theta until we reach the level for the "-2LLR" which return from the user supplied function fun.

Usage

```
findLnew(step=0.01, initStep=0, fun, MLE, level=qchisq(0.95,df=1),
          tol=.Machine$double.eps^0.5,...)
```

Arguments

step	Search step. Must > 0.
initStep	The initial step from MLE. May be used if we knew the bound is far away from MLE. This help to speed up things. Should be >=0.
fun	The function that should return "-2LLR".
MLE	The MLE of the parameter.
level	The level of the confidence. Default to 3.84 which is 95 percent confidence.
tol	The error bound for achieving the level given.
...	Any additional input to be passed to fun.

Details

This function is similar to findUnew().

Value

It returns a list containing

Low	Lower bound of the confidence interval.
FstepL	The error when search for Lower bound.
Lvalue	The final likelihood ratio value for Lower bound. Should =~ level.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

findULNEW

Finding the Upper and Lower bound of a confidence interval for theta by repeatedly testing the hypothesis for the parameter theta.

Description

This function try to find the Upper and Lower bound of a confidence interval by repeatedly testing the hypothesis for the parameter theta until we reach the given level for the "-2LLR" which is returned from the user supplied function fun.

Usage

```
findULNEW(step=0.01, initStep=0, fun, MLE, level=qchisq(0.95,df=1),
          tol=.Machine$double.eps^0.5,...)
```

Arguments

step	Search step. Must > 0.
initStep	The initial step from MLE. May be used if we knew the bound is far away from MLE. This help to speed up things. Should be >=0.
fun	The function that should return "-2LLR".
MLE	The MLE of the parameter.
level	The level of the confidence. Default to 3.84 which is 95 percent confidence (assume df=1).
tol	The error bound for achieving the level given.
...	Any additional input to be passed to fun.

Details

This function just combines the two functions findUnew() and findLnew().

Value

It returns a list containing

Low	Lower bound of the confidence interval.
Up	Upper bound of the confidence interval.
FstepL	The error when search for Lower bound.
FstepU	The error when search for Upper bound.
Lvalue	The final likelihood ratio value for Lower bound. Should = level.
Uvalue	The final likelihood ratio value for Upper bound. Should = level.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

findUnew	<i>Finding the Upper bound of a confidence interval for theta by repeatedly testing the hypothesis for the parameter theta.</i>
----------	---

Description

This function try to find the Upper bound of a confidence interval by repeatedly testing the hypothesis for the parameter theta until we reach the level for the "-2LLR" which return from the user supplied function fun.

Usage

```
findUnew(step=0.01, initStep=0, fun, MLE, level=qchisq(0.95,df=1),
         tol=.Machine$double.eps^0.5,...)
```

Arguments

<code>step</code>	Search step. Must > 0 .
<code>initStep</code>	The initial step from MLE. May be used if we knew the bound is far away from MLE. This help to speed up things. Should be ≥ 0 .
<code>fun</code>	The user supplied function that should return "-2LLR".
<code>MLE</code>	The MLE of the parameter. An approximate value should be OK.
<code>level</code>	The level of the confidence. Default to 3.84 which is 95 percent confidence.
<code>tol</code>	The error bound for achieving the level given.
<code>...</code>	Any additional input to be passed to fun.

Details

This function is similar to `findLnew( )`.

The search is separate (for upper and lower) since Upper and Lower bound may behave differently and require different nuisance parameters inputs (in `...`).

Value

It returns a list containing

<code>Up</code>	Upper bound of the confidence interval.
<code>FstepU</code>	The error when search for Upper bound.
<code>Uvalue</code>	The final likelihood ratio value for Upper bound. Should $\approx$ level.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

myEstPaucT	<i>Given the x, y 2-sample data, first estimate the (1-partial)-th quantile of X sample, then estimate the pAUC(0, partial), with the plug-in estimated quantile.</i>
------------	---

Description

This function computes the estimator using smoothed Indicator function $I[x < y]$ which is a 3rd order polynomial.

eps is a scalar, must > 0 . It is the smoothing window width for indicator function when compare x - y . *epsT* is a scalar, must > 0 . It is the smoothing window width for estimating quantile function when compare x with τ .

Usage

```
myEstPaucT(x, y, partial, eps=0.05, epsT=(length(x))(-0.75))
```

Arguments

<i>x</i>	a vector of observations, length m , for the first sample. Test-results with healthy subjects.
<i>y</i>	a vector of observations, length n , for the second sample. Test-results with disease subjects.
<i>partial</i>	The probability in $\text{pAUC}(0, \text{partial})$.
<i>eps</i>	The smoothing window width, for indicator $I[x < y]$. Must > 0 .
<i>epsT</i>	The smoothing window width for the quantile estimation. Must > 0 .

Details

This function gives the estimators that are consistent with our smoothing used in the computation of empirical likelihood. Typically the smoother for quantile should be a bit "smoother" than usual.

Known problem: when input *partial* is too close to 1 or 0, it will fail. When *partial* is equal to 1, then the pAUC reduces to AUC, which can be estimated easily, as the example below shows.

Why not also give the AUC estimator? Maybe it is too easy. See example below.

Value

This function returns a list, with

"tau(1-partial)"

The estimator for the (1-partial)-th quantile of X-distribution,

and

"Pauc(0, partial)"

The estimated pAUC.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
#### To get an estimator of the AUC (not pAUC), using our smooth3( ), we do
sum(smooth3(x=x, y=y))/(length(x)*length(y))
#### We should get AUC = 0.75.
#### To get the estimator of the pAUC(0, 0.3) AND the 70th quantile of x sample
myEstPaucT(x=x, y=y, partial=0.3)
#### We should get estimator tau(1-0.3)=239.9474 and pAUC(0, 0.3)=0.1416667.
```

New.el2.test

One Iteration of Computing Paired Two Sample Constrained NPMLE.

Description

This function computes the two sample Constrained Data NPMLE: u vectoe and v vector.

Usage

```
New.el2.test(u0, v0, indicmat, tol.H0, step=0.001)
```

Arguments

u0	The constrained NPMLE from initial probability for sample one.
v0	given constrained NPMLE, initial probability for sample two
indicmat	A Matrix of (smoothed) indicator values: $I[x[i] < y[j]] - \theta$.
tol.H0	a positive number for solve constrained NPMLE tolerance.
step	a positive number. Used to approximate the derivative of lambda function at 0.

Details

The constraint is specified by matrix indicmat in

$$u \% * \%indicmat \% * \%t(v) = 0$$

The empirical likelihood we used here is defined as

$$EL = \prod_{i=1}^m v_i \prod_{j=1}^n \nu_j ; \quad \sum v_i = 1, \quad \sum \nu_j = 1.$$

Value

A list that is the same as `el2.cen.EMs()` from `emplik2` package. Which contains

<code>u</code>	The new constrained NPMLE. X sample.
<code>v</code>	The new constrained NPMLE. Y sample.
<code>lam</code>	The lambda value.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

quantONE

Smoothed quantile estimation from the given x-sample.

Description

This function computes the smoothed quantile estimate, using the smoothing function `smooth3`. (or it can be changed easily) Otherwise it is similar to R function `quantile()`. Compare to `quantile(x, prob, type=9)`.

myeps is a scalar, must > 0 . It is the smoothing window width.

Usage

```
quantONE(x, prob, myeps=(length(x))(-0.75))
```

Arguments

<code>x</code>	a vector of observations, length <code>m</code> , the sample.
<code>prob</code>	a probability.
<code>myeps</code>	The smoothing window width, must > 0 .

Details

This function is called by myEstPaucT. It is listed here because the user may find it useful elsewhere.

Known problems: when the input prob is too close to 0 or 1 (distance less than 0.03), the computation will stop. Also, if the solution to the equation

$$\tau \mid \frac{1}{m} \sum_{i=1}^m \text{smooth3vec}(X_i, \tau, \text{myeps}) = \text{prob}$$

is not unique, this function only returns one of the solutions.

Value

The function quantONE returns a scalar that is the estimated (prob)-th quantile of X distribution.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
#### To estimate the 70-th percentile of x distribution:
quantONE(x=x, prob=0.7)
#### we should get 239.9474.
```

smooth0

Non-Smoothed indicator function $0.5I[x=y] + I[x < y]$.

Description

This function computes the non-smoothed Indicator function $0.5I[x=y] + I[x < y]$.

Usage

```
smooth0(x, y)
```

Arguments

x a vector of observations, length m, for the first sample.
y a vector of observations, length n, for the second sample.

Details

This function is used in the original AUC computation (non-smoothed). You may achieve the same result with a (data dependent) small `eps` in the function `smooth3(x,y,eps)`. But this is faster and no `eps` to worry about. It is listed here because users may find it useful.

Value

`smooth0( )` returns a matrix of dimension `ncol=length(y)`, `nrow=length(x)`. The entry of the matrix are values of $0.5I[x[i] = y[j]] + I[x[i] < y[j]]$.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

smooth3	<i>Smoothed indicator function $I[x < y]$, which is the integration of the Epanechnikov kernel.</i>
---------	---

Description

This function computes the smoothed Indicator function $I[x < y]$ using a 3rd order polynomial.

If $|x-y| > \text{eps}$ then the result is the same as the indicator function $I[x < y]$ (either 0 or 1). For $|x-y| < \text{eps}$, it is a 3rd order polynomial.

`eps` is a scalar, must > 0 . It is the smoothing window width.

Usage

```
smooth3(x, y, eps=0.05)
```

Arguments

<code>x</code>	a vector of observations, length <code>m</code> , for the first sample.
<code>y</code>	a vector of observations, length <code>n</code> , for the second sample.
<code>eps</code>	The smoothing window width, must > 0 .

Details

This function is used in many places to replace an indicator function $I[x < y]$. For example, when estimating the AUC. It is listed here because users may find it useful elsewhere.

Value

smooth3() returns a matrix of dimension $\text{ncol}=\text{length}(y)$, $\text{nrow}=\text{length}(x)$. The entry of the matrix are smoothed values of $I[x[i] < y[j]]$.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

smooth3vec	<i>Smoothed indicator function $I[x < \text{const}]$, which is the integration of the Epanechnikov kernel.</i>
------------	--

Description

This function computes the smoothed Indicator function $I[x < \text{const}]$ using a 3rd order polynomial. If $|x - \text{const}| > \text{eps}$ then the result is the same as the indicator function $I[x < \text{const}]$ (either 0 or 1). For $|x - \text{const}| < \text{eps}$, it is a 3rd order polynomial.

eps is a scalar, must > 0 . It is the smoothing window width.

Usage

```
smooth3vec(x, const, eps=0.05)
```

Arguments

x	a vector of observations, length m, for the first sample.
const	a single number.
eps	The smoothing window width, must be > 0 . Ideally this should be sample size dependent.

Details

This function is similar to `smooth3` but only compare the `x` vector to a single number and thus returns a vector instead of matrix. You may also use the `smooth3()` with a bit care, for that matter, but this vector version should be faster and save memory. It is listed here because the user may find it useful elsewhere.

We used this function to estimate the quantile from the `x`-sample.

Value

`smooth3vec` returns a vector of `length=length(x)`. The entry of the vector are smoothed values of $I[x[i] < \text{const}]$.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

smooth5vec	<i>Smoothed indicator function $I[x < \text{const}]$, which is the integration of the Quartic kernal.</i>
------------	---

Description

This function computes the smoothed Indicator function $I[x < \text{const}]$ using a 5th order polynomial. If $|x - \text{const}| > \text{eps}$ then the result is the same as the indicator function $I[x < \text{const}]$ (either 0 or 1). For $|x - \text{const}| < \text{eps}$, it is a 5th order polynomial. *eps* is a scalar, must > 0 . It is the smoothing window width.

Usage

```
smooth5vec(x, const, eps=0.05)
```

Arguments

<code>x</code>	a vector of observations, length <code>m</code> , for the first sample.
<code>const</code>	a single number.
<code>eps</code>	The smoothing window width, must be > 0 . Ideally, this should be sample size dependent.

Details

This function is twice continuously differentiable, smoother than smooth3vec. It is listed here because the user may need extra smoothness (compare to smooth3vec) and may find it useful elsewhere.

Value

smooth5vec returns a vector of length=length(x). The entry of the vector are smoothed values of $I[x[i] < \text{const}]$.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

smoothLvec	<i>Smoothed indicator function $I[x < \text{const}]$, linear connecting the 1 and 0 on $[-\text{eps}, \text{eps}]$.</i>
------------	--

Description

This function computes the smoothed Indicator function $I[x < \text{const}]$ using a liare.

If $|x - \text{const}| > \text{eps}$ then the result is the same as the indicator function $I[x < \text{const}]$ (either 0 or 1). For $|x - \text{const}| < \text{eps}$, it is a linear function.

eps is a scalar, must > 0 . It is the smoothing window width.

Usage

```
smoothLvec(x, const, eps=0.05)
```

Arguments

x	a vector of observations, length m, for the first sample.
const	a single number.
eps	The smoothing window width, must be > 0 . Ideally this should be sample size dependent.

Details

This function is similar to `smooth3vec` but only compare the `x` vector to a single number and thus returns a vector instead of matrix. You may also use the `smooth3()` with a bit care, for that matter, but this vector version should be faster and save memory. It is listed here because the user may find it useful elsewhere.

We used this function to estimate the quantile from the `x`-sample.

Value

`smoothLvec` returns a vector of `length=length(x)`. The entry of the vector are smoothed values of $I[x[i] < \text{const}]$.

Author(s)

Mai Zhou <maizhou@gmail.com>.

References

Zhao, Y., Ding, X. and Zhou (2021). Confidence Intervals of AUC and pAUC by Empirical Likelihood. Tech Report. <https://www.ms.uky.edu/~mai/research/eAUC1.pdf>

Examples

```
y <- c(10, 209, 273, 279, 324, 391, 566, 785)
x <- c(21, 38, 39, 51, 77, 185, 240, 289, 524)
```

Index

* **nonparametric**

- EL2paucT1T2, [2](#)
- el2test4auc, [3](#)
- el2testPauc, [5](#)
- el2testPaucT, [6](#)
- eltest4aucONE, [7](#)
- eltest4diff2auc, [9](#)
- eltest4paucONE, [10](#)
- eltest4paucT, [11](#)
- findLnew, [13](#)
- findULNEW, [14](#)
- findUnew, [15](#)
- myEstPaucT, [17](#)
- New.el2.test, [18](#)
- quantONE, [19](#)
- smooth0, [20](#)
- smooth3, [21](#)
- smooth3vec, [22](#)
- smooth5vec, [23](#)
- smoothLvec, [24](#)

- EL2paucT1T2, [2](#)
- el2test4auc, [3](#)
- el2testPauc, [5](#)
- el2testPaucT, [6](#)
- eltest4aucONE, [7](#)
- eltest4diff2auc, [9](#)
- eltest4paucONE, [10](#)
- eltest4paucT, [11](#)

- findLnew, [13](#)
- findULNEW, [14](#)
- findUnew, [15](#)

- myEstPaucT, [17](#)

- New.el2.test, [18](#)

- quantONE, [19](#)

- smooth0, [20](#)

- smooth3, [21](#)
- smooth3vec, [22](#)
- smooth5vec, [23](#)
- smoothLvec, [24](#)